AD-A058 093 AIR FORCE WEAPONS LAB KIRTLAND AFB N MEX F/G 9/5

COMPARISON STUDY OF THE FIVE TRANSISTOR-TRANSISTOR-LOGIC (TTL) --ETC(U)

MAY 78 M G KNOLL

UNCLASSIFIED AFWL-TR-78-5 NL

1 OF 2

AD A058 093






MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU

AFWL-TR-78-5

LEVEL II

AFW
78

12

ADA058093

# COMPARISON STUDY OF THE FIVE TRANSISTO
# TRANSISTOR-LOGIC (TTL) FAMILIES AND EMIT
# COUPLED LOGIC (ECL)

AD No.___
DDC FILE COPY

May 1978



Final Report

Approved for public release; distribution unlimited.

This research was sponsored by the Defense Nuclear Agency un
Subtask Z99QAXTB029, Work Unit 62, Radiation Characterizatio
of MSI/LSI.

Prepared for
Director
DEFENSE NUCLEAR AGENCY
Washington, DC 20305

AIR FORCE WEAPONS LABORATORY
Air Force Systems Command
Kirtland Air Force Base, NM 87117

78 07 27 038

AFWL-TR-78-5

This final report was prepared by the Air Force Weapons Laboratory, Kirtland Air Force Base, New Mexico under Job Order WDNE2001. Lt Michael Knoll was the Laboratory Project Officer-in-Charge.



This report has been reviewed by the Office of Information (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

Michael G Knoll

MICHAEL G. KNOLL,
1Lt, USAF
Project Officer

FOR THE COMMANDER

Aaron B Loggins

AARON B. LOGGINS,
Lt Col, USAF
Transient Radiation Effects Branch

Donald A Dowler

DONALD A. DOWLER
Colonel, USAF
Chief, Electromagnetics Division

DO NOT RETURN THIS COPY. RETAIN OR DESTROY.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

## REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER
14 AFWL-TR-78-5

2. GOVT ACCESSION NO.

3. RECIPIENT'S CATALOG NUMBER

4. TITLE (and Subtitle)
6 COMPARISON STUDY OF THE FIVE TRANSISTOR-TRANSISTOR-LOGIC (TTL) FAMILIES AND EMITTER COUPLED LOGIC (ECL).

5. TYPE OF REPORT & PERIOD COVERED
9 Final Report.

6. PERFORMING ORG. REPORT NUMBER

7. AUTHOR(s)
10 Michael G. Knoll

8. CONTRACT OR GRANT NUMBER(s)
16 WDNE
17 20

9. PERFORMING ORGANIZATION NAME AND ADDRESS
Air Force Weapons Laboratory
Kirtland Air Force Base, New Mexico 87117

10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Program Element: 62704H
JON: WDNE2001

11. CONTROLLING OFFICE NAME AND ADDRESS
Director
Defense Nuclear Agency
Washington, D.C. 20305

12. REPORT DATE
11 May 1978

13. NUMBER OF PAGES
100 12 93p.

14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)
Air Force Weapons Laboratory
Kirtland Air Force Base, New Mexico 87117

15. SECURITY CLASS (of this report)
UNCLASSIFIED

15a. DECLASSIFICATION DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

This research was sponsored by the Defense Nuclear Agency under Subtask Z99QAXTB029, Work Unit 62, Radiation Characterization of MSI/LSI.

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

| | |
|---|---|
| Logic Circuits | Neutron |
| Integrated Circuits | Total Dose |
| Bipolar Systems | Test Methods |
| Radiation Tests | |
| Dose Rate | |

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

This report describes the radiation test response of the five transistor-transistor-logic (TTL) technologies and the emitter-coupled-logic (ECL) technology. The five TTL technologies evaluated were Standard, High Speed, Low Power, Low Power Schottky, and Schottky. Quad dual input NAND (TTL) or NOR (ECL) gates and dual D flip-flops from each technology were tested. The devices were characterized for gamma dose-rate logic upset, total gamma dose survivability, and neutron fluence survivability. The data has been analyzed to provide a comparison of each logic technology's radiation response.

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

013150

78 07 27 038

CONTENTS

## SECTION I

## INTRODUCTION

The objective of this study was to provide a comparative analysis of the radiation response of the TTL (transistor-transistor-logic) and ECL (emitter-coupled-logic) devices listed in table 1. This table is comprised of the five TTL families and two types of ECL gates. The five TTL families are Standard, High Speed, Low Power, Low Power Schottky, and Schottky. Quad dual input NAND (TTL) or NOR (ECL) gates and Dual D flip-flops from each TTL family and ECL type were characterized. The three types of radiation tests performed on these devices were gamma dose-rate logic upset, total gamma dose survivability, and neutron fluence survivability.

The experimental low power Schottky NAND gates listed in table 1 were produced under an Air Force Weapons Laboratory (AFWL) contract F29601-73-C-0048, "Bipolar MSI (Medium Scale Integration) Hardening Study." These NAND gates are dielectrically isolated, and have shallow junctioned arsenic doped emitters and diode photocurrent compensation.

The difference in performance and circuit operation of the five TTL families and the ECL gates is presented in appendix A.

Table 1

LIST OF DEVICES TESTED

| Function | Device | Type |
| --- | --- | --- |
| TTL NAND | SN5400J | TI Standard |
| TTL NAND | SN54H00J | TI High Speed |
| TTL NAND | SN54L00J | TI Low Power |
| TTL NAND | SN54S00J | TI Schottky |
| TTL NAND | SN54LS00T | TI Low Power Schottky |
| TTL NAND | SN74LS00J | TI Low Power Schottky |
| TTL NAND | Experimental* | TI Low Power Schottky |
| ECL NOR | 950459 | Fairchild |
| ECL NOR | MC10102L | Motorola |
| TTL D Flip-Flop | SN5474J | TI Standard |
| TTL D Flip-Flop | SN54H74J | TI High Speed |
| TTL D Flip-Flop | SN54L74J | TI Low Power |
| TTL D Flip-Flop | SN54S74J | TI Schottky |
| TTL D Flip-Flop | SN54LS74J | TI Low Power Schottky |
| ECL D Flip-Flop | 952859 | Fairchild |
| ECL D Flip-Flop | MC10131L | Motorola |

* The devices labeled "Experimental" were produced by Texas Instruments (TI) for experimental purposes. The devices contain arsenic doped emitters and are not commercially available.

## SECTION II

## ELECTRICAL CHARACTERIZATION TESTS

The test devices were electrically characterized before they were subjected to the radiation environments. The electrical tests were performed on a Fairchild 5000 integrated circuit tester. All the NAND and NOR gates listed in table 1 were subjected to approximately the same electrical tests. Likewise, all the D flip-flops were subjected to similar electrical tests. The electrical tests performed on the devices were output voltage, power supply current, input current, propagation delay times, and short circuit output current (not performed on ECL devices). The output high and output low voltages were measured on the TTL devices with the following source and sink currents applied:

| Device Type | Source Current | Sink Current |
|---|---|---|
| Standard | 400 μA | 16 mA |
| High Speed | 1 mA | 20 mA |
| Schottky | 1 mA | 20 mA |
| Low Power | 100 μA | 2 mA |
| Low Power Schottky | 400 μA | 4 mA |

These sink and source currents represent a fanout of ten. The electrical tests were performed on the ECL devices with each output loaded with a 50-ohm resistor connected to a minus-two-volt power supply.

Appendix B contains a detailed description of the electrical characterization tests performed on the TTL and ECL devices.

## SECTION III

## TRANSIENT RADIATION TESTS

### 1. TEST PROCEDURES

Figure 1 shows the schematic of the gene[illegible] test setup used for the transient radiation logic upset tests. The TTL load is used to simulate an approximate fanout of ten. The values of $R_L$ for the different TTL families are:

Standard, High Speed, and Schottky - $R_L = 200\Omega$

Low Power and Low Power Schottky - $R_L = 800\Omega$

A 0.1 μF capacitor is applied in parallel with the power supplies to hold them constant during the radiation pulse. Fifty-ohm terminators were used at the oscilloscopes to reduce reflections down the coaxial cables.

The LH0033C unity gain line drivers were used with a divide-by-two resistive divider to provide the necessary drive for the 50-ohm terminated coaxial cables. The NAND and NOR gates were irradiated with both inputs DC biased either at their input high voltage or their input low voltage to get the necessary output low and high voltages, respectively. The D flip-flops were biased dynamically during the radiation pulse as illustrated in figure 2.

The transient radiation tests were performed at the AFWL Flash X-ray facility. The pulse width produced by this FXR is approximately 20 nanoseconds. The output voltage of the devices was monitored during the radiation pulse. Logic upset threshold for the TTL NAND gates is defined as 0.8 volt for the output low voltage and 2.0 volts for the output high




FIGURE 1. TRANSIENT RADIATION TEST SCHEMATIC

Figure 1. Transient Radiation Test Schematic.




FIGURE 2. D FLIP-FLOP BIAS CONDITIONS DURING THE TRANSIENT RADIATION TESTS

Figure 2. D Flip-Flop Bias Conditions During the Transient Radiation Tests

voltage. For the ECL NOR gates the logic upset threshold is defined as - 1.100 volts and - 1.500 volts for output high and output low voltages, respectively. The D flip-flops logic upset threshold occurs when the radiation pulse causes the flip-flop to change state. Three devices of each device type were tested. The devices were tested at the following transient dose rates:

| NAND and NOR Gates | D Flip-Flops |
| --- | --- |
| $1.8 \times 10^8$ rad(Si)/s | $2 \times 10^8$ rad(Si)/s |
| $3.6 \times 10^8$ rad(Si)/s | $4.4 \times 10^8$ rad(Si)/s |
| $7.2 \times 10^8$ rad(Si)/s | $7 \times 10^8$ rad(Si)/s |
| $1.4 \times 10^9$ rad(Si)/s | |
| $3.2 \times 10^9$ rad(Si)/s | |
| $6 \times 10^9$ rad(Si)/s | |

2. TEST RESULTS

All three devices of each particular type exhibited approximately the same transient radiation response. The largest tested transient dose-rates at which all the tested devices operated without logic upset are shown below:

| Device Type | Dose-Rate |
| --- | --- |
| SN5400J | $7.2 \times 10^8$ rad(Si)/s |
| SN54H00J | $7.2 \times 10^8$ rad(Si)/s |
| SN54S00J | $7.2 \times 10^8$ rad(Si)/s |
| SN54L00J | $3.6 \times 10^8$ rad(Si)/s |
| SN54LS00T | $3.6 \times 10^8$ rad(Si)/s |
| Experimental | $3.2 \times 10^9$ rad(Si)/s |

| Device Type | Dose-Rate |
|---|---|
| 950459 | $3.6 \times 10^8$ rad(Si)/s |
| MC10102L | $3.6 \times 10^8$ rad(Si)/s |
| SN5474J | $4.4 \times 10^8$ rad(Si)/s |
| SN54H74J | $4.4 \times 10^8$ rad(Si)/s |
| SN54S74J | $4.4 \times 10^8$ rad(Si)/s |
| SN54L74J | $2 \times 10^8$ rad(Si)/s |
| SN54LS74J | $2 \times 10^8$ rad(Si)/s |
| 952859 | $4.4 \times 10^8$ rad(Si)/s |
| MC10131L | $4.4 \times 10^8$ rad(Si)/s |

Graphs illustrating the complete photoresponse of the TTL NAND and ECL NOR gates are shown in figures 3 through 10.

Appendix C contains oscilloscope photographs showing the radiation response of some of the devices tested.

The Standard, High Speed, and Schottky TTL devices are more resistant to the transient ionizing radiation than the Low Power and Low Poser Schottky TTL devices. The higher current densities of the Standard, High Speed, and Schottky TTL devices will sweep out the hole-electron pairs generated during the transient radiation pulse more efficiently than the lower current densities of the Low Power TTL devices. Similarly, since ECL operates at high current densities, the ECL D flip-flops exhibit the same failure threshold as the Standard, High Speed, and Schottky TTL D flip-flops. However, the ECL NOR gates exhibited a lower failure threshold than the Standard, High Speed, and Schottky TTL NAND gates. This discrepancy

may be due to the failure thresholds being defined too conservatively. The experimental arsenic doped emitter TTL NAND gates produced by Texas Instruments were an order of magnitude harder to the transient ionizing radiation than the equivalent Low Power Schottky devices (SN54LS00T). These experimental gates are dielectrically isolated and have extremely small geometries and diode photocurrent compensation. These factors result in the increased dose-rate hardness.

The NAND gates are harder than the D flip-flops of the same TTL technology. The D flip-flop is softer to the radiation pulse because after the clock pulse, the D flip-flop is a memory device (see figure 2). Therefore, the D flip-flop will be more susceptible to a perturbation caused by the transient radiation pulse than the NAND gate, whose output is directly dependent on the input during the pulse.




Figure 3. Transient Radiation Response of TTL SN5400J Nand Gate




FIGURE 4. TRANSIENT RADIATION RESPONSE OF TTL SN54H00J NAND GATE

Figure 4. Transient Radiation Response of TTL SN54H00J Nand Gate.




Figure 5. Transient Radiation Response of TTL SN5400J Nand Gate.




Figure 6. Transient Radiation Response of TTL Sn54L00J Nand Gate




Figure 7. Transient Radiation Response of TTL SN54LS00J Nand Gate.




Figure 8. Transient Radiation Response of TTL Experimental Nand Gate.




FIGURE 9. TRANSIENT RADIATION RESPONSE OF ECL MC10102L NOR GATE

Figure 9. Transient Radiation Response of ECL MC10102L NOR Gate.




Figure 10. Transient Radiation Response of ECL 950459 NOR Gate.

## SECTION IV

## TOTAL GAMMA DOSE RADIATION TESTS

Three devices from each device type listed in table 1 were irradiated with the Cs-137 gamma ray source at Sandia Laboratories. The devices were exposed to a total gamma dose of approximately 1.5 X $10^6$ rads(Si). The TTL devices were DC biased with + 5 volts on VCC and all inputs open during the radiation. The ECL devices were irradiated with no bias applied. The ECL devices were not biased due to the large power consumption of the devices and the heat produced by the Cs-137 source. The devices were electrically tested before and after the total gamma dose irradiation. There was no appreciable difference in the preirradiated tests and the postirradiated tests. This is reasonable since the displacement effect in bulk silicon caused by gamma rays is minimal.

## SECTION V

## NEUTRON FLUENCE RADIATION TESTS

### 1. TEST PROCEDURES

Three or four devices from each device type listed in table 1 were irradiated with the fast burst reactor at Sandia Laboratories in incremental neutron fluence levels. After each incremental radiation dose was reached, the devices were electrically tested. The cumulative neutron fluence levels at which the devices were electrically tested were approximately $2.8 \times 10^{12}$ n/cm$^2$, $6.9 \times 10^{13}$ n/cm$^2$, $1.4 \times 10^{14}$ n/cm$^2$, $7.3 \times 10^{14}$ n/cm$^2$, $1.2 \times 10^{15}$ n/cm$^2$, and $2 \times 10^{15}$ n/cm$^2$. These fluence levels are 1 MeV equivalent. Approximately 80 devices were irradiated simultaneously with no electrical bias applied to them. Output voltage failure thresholds for these tests are the same as defined for the transient radiation tests.

### 2. TEST RESULTS

Appendix D contains the neutron fluence test data that were gathered on the devices listed in table 1. These data are presented in the form of tables. Upon examination of these data, it is apparent that the neutron fluence survivability threshold for a particular device type is approximately the same for the NAND or NOR gates as for the D flip-flops of the same type. The largest tested neutron fluences at which all the tested devices will operate before the output voltage failure threshold occurs are shown below:

| | |
|---|---|
| Standard TTL (SN5400J and SN5474J) | = $1.4 \times 10^{14}$ n/cm$^2$ |
| High Speed TTL (SN54H00J and SN54H74J) | = $4.6 \times 10^{14}$ n/cm$^2$ |

| | | |
|---|---|---|
| Schottky TTL (SN54S00J and SN54S74J) | = | $1.2 \times 10^{15}$ n/cm$^2$ |
| Low Power TTL (SN54L00J and SN54L74J) | = | $1.4 \times 10^{14}$ n/cm$^2$ |
| Low Power Schottky TTL (SN54LS00T and SN54L574J) | = | $1.4 \times 10^{14}$ n/cm$^2$ |
| Experimental TTL | = | $7.3 \times 10^{14}$ n/cm$^2$ |
| Fairchild ECL (950459 and 952859) | = | $4.6 \times 10^{14}$ n/cm$^2$ |
| Motorola ECL (MC10102L and MC10131L) | = | $4.6 \times 10^{14}$ n/cm$^2$ |

All the TTL devices failed when the output low voltage became larger than the failure threshold. Figure 11 provides graphs of the averaged output voltage of the different TTL families versus neutron fluence. The Fairchild 5000 was not allowed to measure greater than 1.638 volts for the output low voltage for the TTL devices. As can be seen from this figure, the degradation of the output voltage is very gradual until the device fails. At the point of failure, the output low voltages rise suddenly. These output low voltage failures in the TTL devices are a result of the neutron-caused beta degradation of Q1 shown in figure 12. When beta is decreased sufficiently by the neutron radiation, the sink current being forced at the output will cause transistor Q1 to come out of saturation and enter the linear region of operation. As a result of the transistor entering the linear region, the collector-emitter voltage ($V_{CE}$), which equals the output low voltage, increases to failure. Since the sink current simulates a fanout of ten, the output low voltage failure thresholds are correct for this worst case condition. However, if the NAND gates were




Figure 11. TTL Output Voltage Versus Neutron Fluence.




Figure 12. Schematic of a Typica' 5400 Series Nand Gate.

tested with a smaller sink current, which is equivalent to a smaller fanout, the output low voltage would not have failed until a higher neutron fluence level. This conclusion cannot directly apply to the TTL flip-flops because one of the internal gates, which does not have the same circuit design as the 5400 series NAND gates, may fail before the output NAND gates of the flip-flop. In ECL gates, the transistors operate primarily in the linear region; therefore, the circuit operation is more sensitive to degradations in beta, and the neutron-caused beta degradation ultimately causes the voltage failures.

The other electrical parameters tested on the devices (power supply current, input current, and propagation delay times) did not deviate appreciably from their maximum or minimum specifications before the output voltage changes caused failure. The input and power supply currents generally decreased due to the beta degradation.

As shown above, the High Speed TTL, Schottky TTL, and ECL gates operated at larger neutron fluences than the lower power TTL devices. The neutron-caused displacement damage in these devices results in decreased recombination lifetime in the base. If the emitter areas and the base transit times of the transistors of the different TTL families are assumed approximately equal, then the recombination rate/carrier is less for devices which operate at higher currents (ref. 1). This explains why the higher-power devices are more resistant to neutron radiation.

---

1. Larin, Frank, Radiation Effects in Semiconductor Devices, New York, NY, John Wiley and Sons, Inc., 1968, pp 159-169.

The Texas Instruments Experimental arsenic doped emitter TTL gates were much harder to the neutron radiation than the equivalent Low Power Schottky devices (SN54LS00T). The very sharp arsenic doped emitter profile in these devices is primarily responsible for the increased neutron hardness. The resulting abrupt emitter-base region width decreases the amount of emitter-base depletion region recombination, resulting in increased neutron hardness (ref. 2).

---

2. Gwyn, G.W., and Gregory, B.L., "Designing Ultrahard Bipolar Transistors", Sandia Laboratories Technical Report, September 1971.

## SECTION VI

## CONCLUSIONS

This report shows that, of the commercially available TTL devices, the High Speed and Schottky devices are the hardest to all the radiation environments. However, as shown by the Experimental NAND gate data, the Low Power Schottky devices can be made very hard with dielectric isolation, small geometries, and arsenic doped emitters. The ECL devices were not harder than the higher-power TTL devices, even though their power consumption is much higher. This is probably due to the linear operation and small noise margin of ECL. As expected, the NAND gates were more resistant to the transient radiation pulse than the D flip-flops, since the flip-flops are memory devices. A variation in the electrical testing of the output voltage would have been beneficial. The output voltage of the devices could have been tested for various fanout sink currents instead of just for a fanout of ten. This would have provided more information to the designer on neutron survivability of the gates for less than worst case conditions.

# APPENDIX A

## TTL AND ECL CIRCUIT PERFORMANCE AND OPERATION

The Five TTL families and ECL gates can be classified as either saturating or nonsaturating logic. The Standard, Low Power and High Speed TTL circuit families belong in the saturating logic category. The TTL Schottky, TTL Low Power Schottky and ECL circuit families belong in the nonsaturating logic category. Nonsaturating logic differs from saturated logic in that the gates in the latter category contain transistors which saturate during circuit operation. As a result, excess charge is stored in the base of the saturated transistor resulting in slower response and propagation delay time.

The Low-Power TTL gate uses less power than the Standard TTL gate, which is shown in figure 12 of the text. This lower power results in slower propagation delay times as compared to the standard TTL technology. Similarly, the High Speed TTL devices use more power than the Standard TTL devices to gain the increased speed. The power consumption and speed are primarily controlled by the resistors in these gates.

The Schottky (S) and Low Power Schottky (LS) TTL technologies are similar to the Low Power and High Speed TTL technologies, respectively. However, the S and LS TTL technology gates contain Schottky clamped transistors to prevent them from entering the saturation region of operation. This results in decreased propagation delay time for a given current due to the absence of base excess charge caused by saturation. The Schottky clamped transistors operate at the edge of saturation when they're in a given state.

The ECL devices are capable of much faster speeds than the TTL technologies. The ECL gates are designed for a small output voltage swing, high power consumption, and linear transistor operation to attain increased speeds over other technologies.

Table A-1 of this appendix illustrates the power speed relationships of these TTL and ECL families.

Table 1. TTL AND ECL POWER SPEED RELATIONSHIPS

| Technology | Typical $P_D$ Gate | Typical $t_p$ Gate |
|---|---|---|
| Standard TTL | 10 mW | 10 ns |
| Low Power TTL | 1 mW | 33 ns |
| High Speed TTL | 22 mW | 6 ns |
| Low Power Schottky TTL | 2 mW | 9.5 ns |
| Schottky TTL | 19 mW | 3 ns |
| ECL (Fairchild 95K series) | 25 mW | 2 ns |

# APPENDIX B

## ELECTRICAL CHARACTERIZATION TESTS

This appendix contains a detailed description of the electrical characterization tests performed on the TTL and ECL devices listed in table 1 of the text. These tests were performed at the Air Force Weapons Laboratory on the Fairchild 5000/5800 Integrated Circuit Tester. Figures B1 through B12 contain the tests performed on the TTL NAND gates and D flip-flops. Figures B13 through B19 contain the tests performed on the ECL NOR gates and D flip-flops.




| $I_{SINK}$ | TTL TYPE |
|---|---|
| 16 mA | STANDARD |
| 20 mA | HIGH SPEED |
| 20 mA | SCHOTTKY |
| 2 mA | LOW POWER |
| 4 mA | LOW POWER SCHOTTKY |

$V_{CC} = 5V$

$V_{IH} = 2V$

Figure 31. TTL Output Low Voltage ($V_{OL}$)




| $I_{SOURCE}$ | TTL TYPE |
|---|---|
| 400 $\mu$A | STANDARD |
| 1 mA | HIGH SPEED |
| 1 mA | SCHOTTKY |
| 100 $\mu$A | LOW POWER |
| 400 $\mu$A | LOW POWER SCHOTTKY |

$V_{IL}$ = .4 V

$V_{CC}$ = 5 V

Figure B2. TTL Output High Voltage ($V_{OH}$)




$V_{CC}$ = 5.5 V

$V_{IN}$ = 5.5 V AND GROUND

Figure B3. TTL Power Supply Current ($I_{CC}$)




$V_{CC}$ = 5.5 V

$V_{IN}$ = 5.5 V AND 2.4 V

Figure B4. TTL Input High Current ($I_{IH}$)




Figure B5. TTL Input Low Current ($I_{IL}$)




Figure B6. TTTL Short Circuit Output Current ($I_{OS}$)




Figure B7. TTL Propagation Delay Times ($T_{PHL}$, $T_{PLH}$)

$I_{SINK}$ AND = SAME AS TTL NAND GATES
$I_{SOURCE}$




$V_{CC} = 5$ V
P = PRESET
D = D
CLK = CLOCK
CLR = CLEAR

TRUTH TABLE

| P | CLR | CLK | D | Q | Q |
|---|---|---|---|---|---|
| 0 | 1 | X | X | 0 | 1 |
| 1 | 0 | X | X | 1 | 0 |
| 1 | 1 | 1* | 0 | 0 | 1 |
| 1 | 1 | 1* | 1 | 1 | 0 |

0 = .8 V
1 = 2 V
*MOMENTARILY APPLY .4 V THEN 2 V
+ DON'T CARE

Figure 38. TTL F/F Output Voltage ($V_{OL}$ and $V_{OH}$)




| TEST | APPLY GND | OPEN |
|---|---|---|
| $I_{CC}$ | CLK, D, P | CLR |
| $I_{CC}$ | CLK, D, CLR | P |

$V_{CC}$=4.5 V

Figure 39 TTL F/F Power Supply Current ($I_{CC}$)




| APPLY 2.4 V AND 5.5 V TEST $I_{IH}$ | APPLY 4.5 V | APPLY GND |
|---|---|---|
| CLK | CLR, D | P |
| CLK | P, D | CLR |
| P | CLR, D | CLK |
| CLR | P | D, CLK * |
| D | P, CLK | CLR |

$V_{CC} = 5.5$ V

*MOMENTARILY APPLY GND THAN 4.5 V

| APPLY .4 V TEST $I_{IL}$ | APPLY 4.5 V | APPLY GND |
|---|---|---|
| CLK | CLR | P, D |
| P | CLR | CLK, D |
| CLR | CLK, D, P | |
| D | CLR, CLK | P |

Figure B10 TTL F/F Input Current ($I_{IN}$, $I_{IL}$)




$V_{CC} = 5.5$ V

$V_{IN} = GND$

Figure B11. TTI F/F Short Circuit Output Current ($I_{OS}$)




Figure B12. TTL F/F Propagation Delay Times ($t_{PHL}$, $t_{PLH}$)




| | $V_{IN1}$ | $V_{IN2}$ | $V_{OUT}$ |
|---|---|---|---|
| CASE I | $V_{IL}$ | $V_{IH}$ | $V_{OH}$ |
| CASE II | $V_{IH}$ | $V_{IL}$ | $V_{OH}$ |
| CASE III | $V_{IH}$ | $V_{IH}$ | $V_{OL}$ |

Figure B13. ECL Output Voltage ($V_{OH}$, $V_{OL}$)




Figure B14. ECL Input Current ($I_{IL}$, $I_{IN}$)




Figure B15. ECL Power Supply Current ($I_{CC}$)




Figure B16. ECL Propagation Delay Time ($t_{PHL}$, $t_{PLH}$)




| P | CLR | CLK | D | Q | $\overline{Q}$ |
|---|---|---|---|---|---|
| $V_{IH}$ | $V_{IL}$ | X | X | 0 | 1 |
| $V_{IL}$ | $V_{IH}$ | X | X | 1 | 0 |
| $V_{IL}$ | $V_{IL}$ | $V_{IH}$* | $V_{IL}$ | 0 | 1 |
| $V_{IL}$ | $V_{IL}$ | $V_{IH}$* | $V_{IH}$ | 1 | 0 |

952859 – $V_{IL} = 4.850\ V$
$V_{IH} = -.810\ V$

MC10131 L – $V_{IL} = -1.700\ V$
$V_{IH} = -.900\ V$

$V_{CC} = GND$ $V_{EE} = -5.2\ V$

*MOMENTARILY APPLY $V_{IL}$ THEN $V_{IH}$

Figure B17. ECL F/F Output Voltage ($V_{OH}$, $V_{OL}$)




Figure 318. ECL F/F Current Measurements ($I_{CC}$, $I_{IH}$, $I_{IL}$)

A. Measure Icc (Power Supply Current

1. All inputs and outputs open
2. Vcc = GND, Vee = 5.2v
3. Measure at Vee

B. Measure IIL (Input Low Current)

1. All inputs = VIL and outputs open.
2. Measure each input separately.
3. Vcc = GND, Vee = 5.2v

C. Measure IIH (Input High Current)

1. All inputs - VIH and outputs open.
2. Measure each input separately.
3. Vcc = GND, Vee = -5.2v




Figure B19. ECL F/F Propagation Delay Time ($t_{PHL}$, $t_{PLH}$)

# APPENDIX C

## PHOTORESPONSE PHOTOGRAPHS

Figures C-1 through C-5 of this appendix illustrate the output photoresponse of the five TTL family NAND gates. These photographs illustrate characteristic dose-rate response of each TTL technology. As can be seen by these pictures, the Low Power and Low Power Schottky TTL technologies have a longer recovery time than the higher power Standard, High Speed and Schottky TTL technologies. The high current densities of the Standard, High Speed, and Schottkv technologies more rapidlv sweepout the hole-electron pairs generated during the transient radiation pulse.

Horizontal = 200 ns/div

Vertical = 0.5 v/div = 1 V div at the device




Output High Voltage ($V_{OH}$)




Output Low Voltage ($V_{OL}$)

Figure C-1. TTL Low Power NAND Gate Photoresponse.

Horizontal = 200 ns/div

Vertical = 0.5 v/div = 1 V/div at the device



Output High Voltage ($V_{OH}$)



Output Low Voltage ($V_{OL}$)

Figure C-2. TTL Low Power Schottky NAND Gate.

Horizontal = 200 ns/div

Vertical = 0.5V/div = 1V/div at the device




Output High Voltage ($V_{OH}$)



Output Low Voltage ($V_{OL}$)

Figure C-3. TTL Standard NAND Gate Photoresponse

Horizontal = 200 ns/div

Vertical = 0.5 V/div = 1.V/div at the device




Output High Voltage ($V_{OH}$)




Output Low Voltage ($V_{OL}$)

Figure C-4. TTL High Speed NAND Gate Photoresponse.

Horizontal = 200 ns/div

Vertical = 0.5 V/div = 1 V/div at the device




*Output High Voltage* ($V_{OH}$)




Output Low Voltage ($V_{OL}$)

Figure C-5. TTL Schottky NAND Gate Photoresponse.

# APPENDIX D

## NEUTRON FLUENCE TEST DATA

This appendix contains the test data gathered on each device exposed to the neutron fluence irradiation. The data resulted from the electrical tests performed on the Fairchild 5000 integrated circuit tester following each incremental neutron irradiation. The data are presented in tables illustrating the specific electrical parameter measurements for each cumulative neutron fluence level. The units for each cumulative neutron fluence level are $n/cm^2$. Each electrical parameter listed shows the worst case measurement for that parameter. For example, each SN5400J NAND gate packaged dip contains four NAND gates. Hence the SN 5400J output low voltage measurements ($V_{OL}$) shown on the table are the highest or worst case measurements of the four gates on that device. The Fairchild 5000 was not allowed to measure a voltage greater than 1.638 volts for the output low voltages of the TTL devices. However, this is sufficient since failure has already occurred at this point.

The measurements made on the SN54L00J devices do not include measurements made at $4.6 \times 10^{14}$ $n/cm^2$ fluence level due to an error. However, measurements were made on the SN54L74J devices at this level. The measurements on the latter device showed that it failed at $4.6 \times 10^{14}$ $n/cm^2$. Thus, these data indicate that the output failure threshold for the low power TTL technology lies between $1.4 \times 10^{14}$ and $4.6 \times 10^{14}$ $n/cm^2$. Also note that the ECL NOR gates were tested at only the higher neutron fluence levels. Since data had already been gathered on the ECL D flip-flops, time was saved by irradiating first at higher neutron fluences. The propagation delay time measurements shown on the tables are not valid for the cumulative neutron fluences at which the output voltages failed.

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE 950459

| TEST | | PRE RAD | .57E+15 | 1.0E+15 |
|---|---|---|---|---|
| VOL | (VOLTS) | -1.661 | -1.596 | -1.528 |
| VOH | (VOLTS) | - .9197 | - .9776 | -1.191 |
| ICC | (MILLIAMPS) | 52.92 | 47.21 | 39.83 |
| I1L | (MILLIAMPS) | 1.712 | 1.716 | 1.789 |
| I1H | (MILLIAMPS) | 2.195 | 2.510 | 2.792 |
| TPHL | (NANOSEC) | 4.12 | 2.97 | 1.05 |
| TPHL | (NANOSEC) | 3.70 | 2.42 | 1.97 |
| TPLH | (NANOSEC) | 3.80 | 3.90 | * |
| TPLH | (NANOSEC) | 3.77 | 3.72 | * |

* Measurements are not valid due to the shift in output voltage.

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE 950459

| TEST | | PRE RAD | .57E+15 | 1.0E+15 |
|---|---|---|---|---|
| VOL | (VOLTS) | -1.688 | -1.627 | -1.559 |
| VOH | (VOLTS) | - .9287 | - .9776 | -1.552 |
| ICC | (MILLIAMPS) | 48.07 | 43.80 | 37.82 |
| I1L | (MILLIAMPS) | 1.569 | 1.566 | 1.584 |
| I1H | (MILLISMPS) | 1.968 | 2.218 | 2.489 |
| TPHL | (NANOSEC) | 3.65 | 2.85 | 1.75 |
| TPHL | (NANOSEC) | 3.40 | 2.57 | 1.57 |
| TPLH | (NANOSEC) | 3.72 | 3.75 | * |
| TPLH | (NANOSEC) | 3.55 | 3.65 | * |

* Measurements are not valid due to the shift in output voltage.

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE 950459

| TEST | | PRE RAD | .57E+15 | 1.0E+15 |
|---|---|---|---|---|
| VOL | (VOLTS) | -1.696 | -1.581 | -1.509 |
| VOH | (VOLTS) | - .9233 | -1.012 | -1.305 |
| ICC | (MILLIAMPS) | 52.36 | 45.70 | 37.49 |
| IIL | (MILLIAMPS) | 1.772 | 1.769 | 1.973 |
| IIH | (MILLIAMPS) | 2.315 | 2.672 | 2.932 |
| TPHL | (NANOSEC) | 3.35 | 2.35 | 1.07 |
| TPHL | (NANOSEC) | 3.77 | 2.10 | 1.00 |
| TPLH | (NANOSEC) | 4.12 | 3.82 | * |
| TPLH | (NANOSEC) | 3.67 | 3.77 | * |

* Measurements are not valid due to the shift in output voltage.

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE MC10102L

| TEST | | PRE RAD | .57E+15 | 1.0E+15 |
|---|---|---|---|---|
| VOL | (VOLTS) | -1.713 | -1.690 | -1.665 |
| VOH | (VOLTS) | - .8993 | - .9516 | -1.117 |
| ICC | (MILLIAMPS) | 21.10 | 19.32 | 18.50 |
| I1L | (MICROAMPS) | 35.04 | 31.66 | 27.69 |
| I1H | (MILLIAMPS) | .1426 | .1623 | .3066 |
| TPHL | (NANOSEC) | 3.00 | 2.60 | 2.50 |
| TPHL | (NANOSEC) | 2.80 | 2.45 | 2.00 |
| TPLH | (NANOSEC) | 1.00 | 1.25 | 1.60 |
| TPLH | (NANOSEC) | 1.00 | 1.40 | 1.90 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE MC10102L

| TEST | | PRE RAD | .57E+15 | 1.0E+15 |
|---|---|---|---|---|
| VOL | (VOLTS) | -1.702 | -1.672 | -1.642 |
| VOH | (VOLTS) | - .9310 | -1.016 | -1.1520 |
| ICC | (MILLIAMPS) | 20.82 | 19.12 | 18.38 |
| IIL | (MICROAMPS) | 70.45 | 65.50 | 61.28 |
| IIH | (MILLIAMPS) | .1400 | .2371 | .3924 |
| TPHL | (NANOSEC) | 3.00 | 2.50 | 1.90 |
| TPHL | (NANOSEC) | 3.20 | 3.00 | 2.40 |
| TPLH | (NANOSEC) | 1.20 | 1.42 | 1.60 |
| TPLH | (NANOSEC) | 1.50 | 2.00 | 2.70 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE MC10102L

| TEST | | PRE RAD | .57E+15 | 1.07E+15 |
|---|---|---|---|---|
| VOL | (VOLTS) | -1.732 | -1.701 | -1.640 |
| VOH | (VOLTS) | - .9090 | -1.010 | -1.276 |
| ICC | (MILLIAMPS) | 20.97 | 19.50 | 18.37 |
| I1L | (MICROAMPS) | 38.99 | 35.63 | 31.51 |
| I1H | (MILLIAMPS) | .1164 | .2115 | .3028 |
| TPHL | (NANOSEC) | 2.70 | 2.53 | 2.50 |
| TPHL | (NANOSEC) | 2.70 | 2.95 | 2.90 |
| TPLH | (NANOSEC) | 1.30 | 1.75 | 1.90 |
| TPLH | (NANOSEC) | 1.00 | 2.00 | 2.30 |

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE SN5400J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .1496 | .1505 | .1696 | .1972 | .2733 | 1.6380 |
| VOH (VOLTS) | 3.234 | 3.233 | 3.212 | 3.197 | 3.145 | 3.126 |
| ICC (MILLIAMPS) | 5.00 | 5.00 | 4.99 | 4.96 | 4.92 | 4.86 |
| IOS (MILLIAMPS) | 38.60 | 38.56 | 37.72 | 37.04 | 25.57 | 18.12 |
| IIL (MILLIAMPS) | 1.130 | 1.129 | 1.124 | 1.120 | 1.104 | 1.089 |
| IIH (MICROAMPS) | 9.72 | 9.62 | 7.70 | 6.36 | 2.87 | 1.63 |
| TPHL (NANOSEC) | 5.22 | 5.35 | 5.62 | 5.47 | 7.62 | 8.82 |
| TPHL (NANOSEC) | 5.52 | 5.65 | 5.65 | 5.70 | 8.16 | 9.25 |
| TPLH (NANOSEC) | 14.85 | 14.90 | 13.12 | 12.40 | 11.25 | 10.22 |
| TPLH (NANOSEC) | 14.75 | 14.80 | 13.30 | 12.05 | 11.55 | 10.60 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN5400J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .1876 | .1879 | .2156 | .2439 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.163 | 3.162 | 3.125 | 3.113 | 3.036 | 3.009 |
| ICC (MILLIAMPS) | 4.62 | 4.62 | 4.60 | 4.59 | 4.5[illegible] | 4.46 |
| IOS (MILLIAMPS) | 35.99 | 35.98 | 34.49 | 33.28 | 15.0[illegible] | 10.32 |
| IIL (MILLIAMPS) | 1.034 | 1.037 | 1.026 | 1.026 | 1.012 | .989 |
| IIH (MICROAMPS) | 2.01 | 1.98 | 1.51 | 1.16 | .3[illegible] | .14 |
| TPHL (NANOSEC) | 6.87 | 6.82 | 7.47 | 7.57 | 12.57 | 15.25 |
| TPHL (NANOSEC) | 6.95 | 7.02 | 7.62 | 8.00 | 13.1[illegible] | 16.75 |
| TPLH (NANOSEC) | 14.67 | 14.65 | 12.92 | 12.15 | 10.80 | 20.72 |
| TPLH (NANOSEC) | 14.70 | 14.42 | 12.90 | 11.85 | 11.15 | 20.72 |

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE SN5400J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .1361 | .1392 | .1604 | .1825 | .3023 | 1.6380 |
| VOH (VOLTS) | 3.240 | 3.224 | 3.214 | 3.201 | 3.134 | 3.118 |
| ICC (MILLIAMPS) | 5.38 | 5.37 | 5.36 | 5.34 | 5.23 | 5.22 |
| IOS (MILLIAMPS) | 34.99 | 34.24 | 34.17 | 33.63 | 23.97 | 16.69 |
| IIL (MILLIAMPS) | 1.208 | 1.200 | 1.200 | 1.196 | 1.180 | 1.161 |
| IIH (MICROAMPS) | 12.07 | 11.64 | 9.06 | 7.07 | 2.58 | 1.31 |
| TPHL (NANOSEC) | 5.47 | 5.62 | 5.95 | 6.05 | 8.72 | 10.15 |
| TPHL (NANOSEC) | 5.55 | 6.07 | 6.22 | 6.05 | 9.02 | 10.82 |
| TPLH (NANOSEC) | 20.35 | 19.22 | 14.85 | 13.25 | 11.07 | 10.70 |
| TPLH (NANOSEC) | 20.42 | 18.77 | 14.85 | 13.22 | 11.40 | 10.70 |

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE SN5474J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2412 | .2382 | .2577 | .2880 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.271 | 3.241 | 3.224 | 3.232 | 3.155 | 3.150 |
| ICC (MILLIAMPS) | 20.55 | 20.51 | 20.45 | 20.36 | 20.07 | 19.76 |
| IOS (MILLIAMPS) | 36.29 | 36.09 | 35.03 | 31.22 | 17.95 | 12.87 |
| IIL (MILLIAMPS) | 4.531 | 4.518 | 4.504 | 4.491 | 4.438 | 4.389 |
| IIH (MICROAMPS) | 2.80 | 2.76 | 2.33 | 1.86 | 1.50 | .48 |
| TPHL (NSEC-CLOCK) | 19.90 | 20.22 | 19.60 | 7.80 | 21.97 | 40.00 |
| TPHL (NSEC-CLEAR) | 24.95 | 25.15 | 24.52 | 25.30 | 28.02 | 40.00 |
| TPLH (NSEC-CLOCK) | 15.20 | 15.60 | 15.40 | 12.80 | 15.20 | 21.50 |
| TPLH (NSEC-PRESET) | 21.37 | 22.02 | 21.50 | 21.80 | 25.40 | 32.70 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN5474J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2647 | .2676 | .2816 | .3124 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.319 | 3.239 | 3.266 | 3.279 | 3.193 | 3.180 |
| ICC (MILLIAMPS) | 18.99 | 18.64 | 18.92 | 18.85 | 18.61 | 18.37 |
| IOS (MILLIAMPS) | 33.92 | 32.02 | 32.80 | 30.33 | 17.45 | 12.59 |
| IIL (MILLIAMPS) | 4.203 | 4.124 | 4.187 | 4.174 | 4.128 | 4.082 |
| IIH (MICROAMPS) | 2.20 | 2.12 | 1.90 | 1.61 | 1.40 | .59 |
| TPHL (NSEC-CLOCK) | 20.00 | 19.80 | 18.92 | 15.50 | 21.70 | 40.00 |
| TPHL (NSEC-CLEAR) | 24.57 | 24.47 | 23.75 | 24.10 | 27.50 | 40.00 |
| TPLH (NSEC-CLOCK) | 14.60 | 14.70 | 14.50 | 11.10 | 14.90 | 21.30 |
| TPLH (NSEC-PRESET) | 20.57 | 21.10 | 20.67 | 21.00 | 24.50 | 29.30 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE SN5474J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2676 | .2719 | .2983 | .3264 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.247 | 3.224 | 3.195 | 3.206 | 3.098 | 3.089 |
| ICC (MILLIAMPS) | 20.10 | 20.05 | 19.96 | 19.91 | 19.53 | 19.29 |
| IOS (MILLIAMPS) | 34.87 | 34.64 | 33.12 | 27.88 | 14.40 | 10.25 |
| IIL (MILLIAMPS) | 4.402 | 4.392 | 4.374 | 4.368 | 4.309 | 4.253 |
| IIH (MICROAMPS) | 2.10 | 1.14 | .96 | .78 | .50 | .14 |
| TPHL (NSEC-CLOCK) | 19.70 | 19.40 | 19.40 | 16.60 | 22.70 | 40.00 |
| TPHL (NSEC-CLEAR) | 24.47 | 24.47 | 24.00 | 23.50 | 29.30 | 40.00 |
| TPLH (NSEC-CLOCK) | 13.90 | 14.40 | 14.10 | 10.60 | 15.10 | 28.40 |
| TPLH (NSEC-PRESET) | 21.17 | 20.40 | 19.90 | 21.40 | 26.40 | 34.80 |

MEASUREMENTS ON DEVICE NUMBER 1. DEVICE TYPE SN54L00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .73E+15 |
|---|---|---|---|---|---|
| VOL (VOLTS) | .1635 | .1641 | .1927 | .2304 | 1.6[illegible]83 |
| VOH (VOLTS) | 3.238 | 3.234 | 3.160 | 3.103 | 2.743 |
| ICC (MILLIAMPS) | .65 | .65 | .64 | .64 | .6 |
| IOS (MILLIAMPS) | 10.71 | 10.51 | 6.01 | 4.09 | .9 |
| IIL (MILLIAMPS) | .150 | .150 | .149 | .148 | .163 |
| IIH (MICROAMPS) | .36 | .35 | .26 | .20 | .0[illegible] |
| TPHL (NANOSEC) | 35.20 | 35.30 | 38.97 | 41.82 | 60.92 |
| TPHL (NANOSEC) | 36.70 | 36.57 | 40.70 | 44.77 | 60.9[illegible] |
| TPLH (NANOSEC) | 19.35 | 18.32 | 41.90 | 44.30 | 60.92 |
| TPLH (NANOSEC) | 19.20 | 19.10 | 40.20 | 44.50 | 60.9 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN[illegible]4L00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .73E+15 |
|---|---|---|---|---|---|
| VOL (VOLTS) | .1533 | .1544 | .1771 | .2015 | 1.6[illegible]80 |
| VOH (VOLTS) | 3.248 | 3.244 | 3.175 | 3.126 | 2.778 |
| ICC (MILLIAMPS) | .44 | .44 | .44 | .44 | .4 |
| IOS (MILLIAMPS) | 9.11 | 9.10 | 7.05 | 4.94 | 1.1[illegible] |
| IIL (MILLIAMPS) | .103 | .103 | .102 | .101 | .0[illegible]7 |
| IIH (MICROAMPS) | .48 | .46 | .37 | .26 | .1 |
| TPHL (NANOSEC) | 38.40 | 38.67 | 40.30 | 41.90 | 54.3[illegible] |
| TPHL (NANOSEC) | 40.67 | 40.77 | 37.60 | 44.60 | 59.27 |
| TPLH (NANOSEC) | 22.60 | 20.37 | 13.37 | 41.90 | 60.0[illegible] |
| TPLH (NANOSEC) | 22.60 | 20.70 | 14.22 | 42.60 | 60.00 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE SN 4L00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .73E+15 |
|---|---|---|---|---|---|
| VOL (VOLTS) | .1555 | .1559 | .1804 | .2051 | 1.6380 |
| VOH (VOLTS) | 3.255 | 3.251 | 3.179 | 3.126 | 2.752 |
| ICC (MILLIAMPS) | .44 | .44 | .43 | .43 | .4[illegible] |
| IOS (MILLIAMPS) | 8.99 | 8.96 | 7.40 | 5.05 | 1.11 |
| IIL (MILLIAMPS) | .103 | .102 | .101 | .101 | .0[illegible]6 |
| IIH (MICROAMPS) | .44 | .42 | .33 | .28 | .1[illegible] |
| TPHL (NANOSEC) | 37.00 | 36.95 | 39.60 | 41.32 | 56.55 |
| TPHL (NANOSEC) | 36.42 | 38.77 | 41.40 | 44.30 | 60.70 |
| TPLH (NANOSEC) | 24.30 | 23.22 | 14.22 | 44.15 | 60.00 |
| TPLH (NANOSEC) | 24.50 | 22.50 | 13.70 | 44.80 | 60.00 |

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE SN54L74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .1728 | .1712 | .1889 | .2083 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.625 | 3.610 | 3.562 | 3.505 | 3.052 | 2.701 |
| ICC (MILLIAMPS) | 1.19 | 1.18 | 1.17 | 1.16 | 1.14 | 1.12 |
| IOS (MILLIAMPS) | 6.93 | 6.74 | 6.28 | 4.53 | 1.64 | 1.08 |
| IIL (MILLIAMPS) | .296 | .293 | .292 | .290 | .286 | .282 |
| IIH (MICROAMPS) | .62 | .61 | .52 | .44 | .40 | .16 |
| TPHL (NSEC-CLOCK) | 151.00 | 153.00 | 160.00 | 169.00 | 235.00 | 310.00 |
| TPHL (NSEC-CLEAR) | 112.00 | 113.00 | 118.00 | 123.00 | 243.00 | 850.00 |
| TPLH (NSEC-CLOCK) | 124.00 | 125.00 | 127.00 | 127.00 | 872.00 | 872.00 |
| TPLH (NSEC-PRESET) | 47.00 | 48.00 | 47.00 | 49.00 | 27.00 | 850.00 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN54L74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .1672 | .1631 | .1783 | .1907 | .9271 | 1.6380 |
| VOH (VOLTS) | 3.613 | 3.610 | 3.560 | 3.508 | 3.162 | 2.750 |
| ICC (MILLIAMPS) | 1.65 | 1.65 | 1.64 | 1.63 | 1.60 | 1.57 |
| IOS (MILLIAMPS) | 7.95 | 7.91 | 7.60 | 5.97 | 2.42 | 1.60 |
| IIL (MILLIAMPS) | .396 | .395 | .393 | .392 | .395 | .379 |
| IIH (MICROAMPS) | 1.50 | 1.38 | 1.26 | 1.15 | .92 | .55 |
| TPHL (NSEC-CLOCK) | 181.00 | 122.00 | 127.00 | 134.00 | 176.00 | 224.00 |
| TPHL (NSEC-CLEAR) | 90.00 | 92.00 | 94.00 | 102.00 | 133.00 | 708.00 |
| TPLH (NSEC-CLOCK) | 98.00 | 100.00 | 101.00 | 104.00 | 872.00 | 871.00 |
| TPLH (NSEC-PRESET) | 42.00 | 43.00 | 42.00 | 44.00 | 90.00 | 850.00 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE SN54L74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .1871 | .1863 | .2037 | .2272 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.645 | 3.644 | 3.572 | 3.502 | 3.065 | 2.675 |
| ICC (MILLIAMPS) | 1.12 | 1.12 | 1.11 | 1.10 | 1.08 | 1.06 |
| IOS (MILLIAMPS) | 6.17 | 6.12 | 5.74 | 4.19 | 1.60 | 1.07 |
| IIL (MILLIAMPS) | .272 | .270 | .268 | .267 | .262 | .257 |
| IIH (MICROAMPS) | .41 | .38 | .32 | .28 | .22 | .11 |
| TPHL (NSEC-CLOCK) | 147.00 | 148.00 | 154.00 | 165.00 | 231.00 | 850.00 |
| TPHL (NSEC-CLEAR) | 109.00 | 110.00 | 115.00 | 250.00 | 262.00 | 850.00 |
| TPLH (NSEC-CLOCK) | 126.00 | 128.00 | 127.00 | 300.00 | 872.00 | 850.00 |
| TPLH (NSEC-PRESET) | 48.00 | 46.00 | 47.00 | 47.00 | 232.00 | 850.00 |

MEASUREMENTS ON DEVICE NUMBER 1. DEVICE TYPE SN54H00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 | .12E+16 |
|---|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2619 | .2627 | .2819 | .2863 | .3465 | .4584 | 1.6380 |
| VOH (VOLTS) | 3.119 | 3.116 | 3.092 | 3.090 | 3.049 | 3.029 | 2.978 |
| ICC (MILLIAMPS) | 11.25 | 11.26 | 11.16 | 11.13 | 10.98 | 10.85 | 10.71 |
| IOS (MILLIAMPS) | 51.60 | 51.91 | 51.28 | 50.89 | 51.24 | 55.71 | 55.61 |
| IIL (MILLIAMPS) | 1.453 | 1.453 | 1.438 | 1.438 | 1.419 | 1.405 | 1.381 |
| IIH (MICROAMPS) | 3.56 | 3.46 | 3.10 | 2.88 | 1.68 | 1.27 | .59 |
| TPHL (NANOSEC) | 5.27 | 5.17 | 5.50 | 5.20 | 6.70 | 6.37 | 10.37 |
| TPHL (NANOSEC) | 5.40 | 5.55 | 5.60 | 5.55 | 6.95 | 6.72 | 11.30 |
| TPLH (NANOSEC) | 10.05 | 9.82 | 9.27 | 8.75 | 8.02 | 7.10 | 6.12 |
| TPLH (NANOSEC) | 10.05 | 9.90 | 9.35 | 8.80 | 8.60 | 7.33 | 6.27 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN=4H00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 | .12E+16 |
|---|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2343 | .2360 | .2481 | .2601 | .3197 | 1.2799 | 1.6383 |
| VOH (VOLTS) | 3.122 | 3.114 | 3.104 | 3.100 | 3.076 | 3.011 | 2.953 |
| ICC (MILLIAMPS) | 12.84 | 12.85 | 12.77 | 12.73 | 12.55 | 12.40 | 12.20 |
| IOS (MILLIAMPS) | 50.27 | 50.59 | 49.96 | 49.56 | 49.87 | 54.23 | 54.08 |
| IIL (MILLIAMPS) | 1.659 | 1.651 | 1.649 | 1.643 | 1.624 | 1.604 | 1.561 |
| IIH (MICROAMPS) | 5.16 | 5.05 | 4.46 | 3.99 | 1.93 | 1.20 | .39 |
| TPHL (NANOSEC) | 6.32 | 6.32 | 6.57 | 6.62 | 8.75 | 8.50 | 14.05 |
| TPHL (NANOSEC) | 6.27 | 9.90 | 7.00 | 6.62 | 8.92 | 8.95 | 15.37 |
| TPLH (NANOSEC) | 10.12 | 10.15 | 9.70 | 9.20 | 8.47 | 7.57 | 8.30 |
| TPLH (NANOSEC) | 9.80 | 9.90 | 9.60 | 9.32 | 8.72 | 7.75 | 8.60 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE SN=4H00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 | .12E+16 |
|---|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2393 | .2399 | .2583 | .2689 | .3224 | 1.0285 | 1.6380 |
| VOH (VOLTS) | 3.120 | 3.119 | 3.076 | 3.091 | 3.040 | 3.025 | 2.966 |
| ICC (MILLIAMPS) | 11.25 | 11.27 | 11.13 | 11.14 | 11.00 | 10.87 | 10.71 |
| IOS (MILLIAMPS) | 51.49 | 51.81 | 51.17 | 50.81 | 51.13 | 55.57 | 55.45 |
| IIL (MILLIAMPS) | 1.448 | 1.451 | 1.424 | 1.435 | 1.420 | 1.404 | 1.367 |
| IIH (MICROAMPS) | 2.80 | 2.72 | 2.40 | 2.16 | 1.08 | .73 | .29 |
| TPHL (NANOSEC) | 5.27 | 5.22 | 5.60 | 5.42 | 7.10 | 6.87 | 11.50 |
| TPHL (NANOSEC) | 5.30 | 5.60 | 5.77 | 5.45 | 7.37 | 7.32 | 12.67 |
| TPLH (NANOSEC) | 9.82 | 9.80 | 9.17 | 8.77 | 7.75 | 7.10 | 7.52 |
| TPLH (NANOSEC) | 9.95 | 9.92 | 9.22 | 9.00 | 7.97 | 7.07 | 7.42 |

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE SN54H74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2399 | .2392 | .2495 | .2695 | .4321 | 1.6380 |
| VOH (VOLTS) | 2.938 | 2.905 | 2.882 | 2.882 | 2.819 | 2.520 |
| ICC (MILLIAMPS) | 32.73 | 32.67 | 32.59 | 32.44 | 31.80 | 51.73 |
| IOS (MILLIAMPS) | 63.01 | 62.84 | 62.21 | 61.45 | 58.60 | 56.29 |
| IIL (MILLIAMPS) | 5.607 | 5.602 | 5.604 | 5.606 | 5.587 | 5.553 |
| IIH (MICROAMPS) | 7.20 | 7.17 | 5.66 | 4.17 | 1.62 | .33 |
| TPHL (NSEC-CLOCK) | 10.90 | 11.20 | 10.45 | 10.92 | 10.00 | 10.62 |
| TPHL (NSEC-CLEAR) | 22.37 | 22.32 | 21.95 | 22.70 | 24.82 | 38.20 |
| TPLH (NSEC-CLOCK) | 26.80 | 30.00 | 25.00 | 29.60 | 19.90 | 16.00 |
| TPLH (NSEC-PRESET) | 14.47 | 14.25 | 13.75 | 14.17 | 12.57 | 10.52 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN54H74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2469 | .2407 | .2539 | .2671 | .3798 | 1.6380 |
| VOH (VOLTS) | 2.906 | 2.883 | 2.867 | 2.873 | 2.868 | 2.641 |
| ICC (MILLIAMPS) | 35.33 | 35.28 | 35.16 | 35.02 | 34.42 | 46.40 |
| IOS (MILLIAMPS) | 66.39 | 66.19 | 65.45 | 64.58 | 61.63 | 59.19 |
| IIL (MILLIAMPS) | 6.148 | 6.142 | 6.144 | 6.142 | 6.125 | 6.088 |
| IIH (MICROAMPS) | 14.00 | 8.97 | 7.33 | 5.85 | 1.91 | .83 |
| TPHL (NSEC-CLOCK) | 9.90 | 9.95 | 9.62 | 10.37 | 9.02 | 9.10 |
| TPHL (NSEC-CLEAR) | 20.55 | 20.32 | 20.25 | 21.02 | 21.62 | 19.70 |
| TPLH (NSEC-CLOCK) | 26.20 | 24.00 | 27.40 | 27.60 | 17.50 | 14.60 |
| TPLH (NSEC-PRESET) | 14.25 | 14.00 | 13.52 | 14.57 | 12.80 | 8.87 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE SN54H74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2359 | .2420 | .2495 | .2668 | .4260 | 1.6380 |
| VOH (VOLTS) | 2.930 | 2.905 | 2.904 | 2.900 | 2.833 | 2.727 |
| ICC (MILLIAMPS) | 35.25 | 35.20 | 35.06 | 34.92 | 34.30 | 39.15 |
| IOS (MILLIAMPS) | 64.32 | 63.43 | 63.42 | 62.65 | 59.84 | 57.45 |
| IIL (MILLIAMPS) | 5.767 | 5.744 | 5.758 | 5.758 | 5.749 | 5.712 |
| IIH (MICROAMPS) | 14.00 | 9.54 | 7.99 | 6.45 | 2.81 | 1.04 |
| TPHL (NSEC-CLOCK) | 14.30 | 14.02 | 13.25 | 14.00 | 12.47 | 10.00 |
| TPHL (NSEC-CLEAR) | 20.92 | 20.80 | 20.42 | 22.15 | 22.25 | 20.00 |
| TPLH (NSEC-CLOCK) | 9.72 | 10.52 | 9.87 | 10.60 | 8.92 | 9.52 |
| TPLH (NSEC-PRESET) | 29.60 | 29.50 | 25.00 | 22.00 | 17.70 | 16.12 |

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE SN54S00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 | .12E+16 | .20E+16 |
|---|---|---|---|---|---|---|---|---|
| VOL (VOLTS) | .3999 | .4027 | .4152 | .4166 | .4[illegible]27 | .4806 | .5216 | 1.5000 |
| VOH (VOLTS) | 3.460 | 3.460 | 3.449 | 3.449 | 3.393 | 3.384 | 3.318 | 3.240 |
| ICC (MILLIAMPS) | 12.79 | 12.79 | 12.73 | 12.72 | 12.6[illegible] | 12.49 | 12.36 | 12.18 |
| IOS (MILLIAMPS) | 51.01 | 50.88 | 50.76 | 50.49 | 50.81 | 55.22 | 54.95 | 56.52 |
| IIL (MILLIAMPS) | 1.636 | 1.638 | 1.630 | 1.631 | 1.620 | 1.614 | 1.601 | 1.586 |
| IIH (MICROAMPS) | .07 | .09 | .09 | .08 | .07 | .09 | .09 | .07 |
| TPHL (NANOSEC) | 2.95 | 2.87 | 2.95 | 2.55 | 3.07 | 2.20 | 3.87 | 5.82 |
| TPHL (NANOSEC) | 3.32 | 3.12 | 3.22 | 3.00 | 3.5[illegible] | 2.65 | 3.80 | 6.40 |
| TPLH (NANOSEC) | 8.77 | 8.70 | 8.77 | 8.32 | 7.87 | 7.15 | 6.90 | 7.62 |
| TPLH (NANOSEC) | 9.22 | 8.72 | 8.62 | 8.42 | 8.1[illegible] | 7.22 | 6.80 | 7.65 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN54S00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 | .12E+16 | .20E+16 |
|---|---|---|---|---|---|---|---|---|
| VOL (VOLTS) | .4167 | .4185 | .4344 | .4368 | .4[illegible]00 | .5116 | .5846 | 1.6380 |
| VOH (VOLTS) | 3.442 | 3.422 | 3.415 | 3.430 | 3.363 | 3.344 | 3.256 | 3.164 |
| ICC (MILLIAMPS) | 13.09 | 13.08 | 13.01 | 13.02 | 12.87 | 12.74 | 12.60 | 12.38 |
| IOS (MILLIAMPS) | 50.67 | 50.54 | 50.41 | 50.13 | 50.3[illegible] | 54.75 | 54.95 | 55.81 |
| IIL (MILLIAMPS) | 1.664 | 1.666 | 1.650 | 1.657 | 1.6[illegible]6 | 1.636 | 1.624 | 1.606 |
| IIH (MICROAMPS) | .07 | .05 | .07 | .09 | .07 | .09 | .07 | .07 |
| TPHL (NANOSEC) | 2.72 | 2.92 | 2.95 | 2.67 | 3.0[illegible] | 2.27 | 3.87 | 7.22 |
| TPHL (NANOSEC) | 3.17 | 3.25 | 3.22 | 3.27 | 3.4[illegible] | 2.67 | 3.80 | 7.57 |
| TPLH (NANOSEC) | 8.70 | 8.60 | 8.45 | 8.20 | 7.55 | 6.77 | 6.90 | 7.1[illegible] |
| TPLH (NANOSEC) | 8.70 | 8.65 | 8.37 | 8.00 | 7.4[illegible] | 6.95 | 6.80 | 7.22 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE SN54S00J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 | .12E+16 | .20E+16 |
|---|---|---|---|---|---|---|---|---|
| VOL (VOLTS) | .4144 | .4195 | .4302 | .4367 | .4[illegible]39 | .5211 | .5841 | 1.6380 |
| VOH (VOLTS) | 3.472 | 3.449 | 3.434 | 3.459 | 3.401 | 3.389 | 3.318 | 3.232 |
| ICC (MILLIAMPS) | 11.63 | 11.59 | 11.51 | 11.56 | 11.43 | 11.32 | 11.20 | 11.00 |
| IOS (MILLIAMPS) | 50.84 | 50.73 | 50.60 | 50.34 | 50.60 | 54.93 | 55.17 | 55.94 |
| IIL (MILLIAMPS) | 1.475 | 1.466 | 1.450 | 1.469 | 1.457 | 1.449 | 1.437 | 1.420 |
| IIH (MICROAMPS) | .08 | .08 | .09 | .11 | .1[illegible] | .11 | .10 | .10 |
| TPHL (NANOSEC) | 3.05 | 3.07 | 3.07 | 2.72 | 3.10 | 2.50 | 3.62 | 6.32 |
| TPHL (NANOSEC) | 3.25 | 3.47 | 3.22 | 3.17 | 3.30 | 2.80 | 3.52 | 6.82 |
| TPLH (NANOSEC) | 8.97 | 8.80 | 8.52 | 8.17 | 7.92 | 7.17 | 6.85 | 7.32 |
| TPLH (NANOSEC) | 8.60 | 8.80 | 8.45 | 8.12 | 7.9[illegible] | 7.00 | 6.90 | 7.25 |

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE SN54S74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 | .12E+16 | .20E+16 |
|---|---|---|---|---|---|---|---|---|
| VOL (VOLTS) | .4431 | .4367 | .4480 | .4582 | .5109 | .5520 | .6064 | 1.6380 |
| VOH (VOLTS) | 2.834 | 2.795 | 2.784 | 2.782 | 2.748 | 2.761 | 2.707 | 2.350 |
| ICC (MILLIAMPS) | 37.24 | 37.20 | 37.11 | 36.97 | 36.35 | 35.90 | 35.37 | 34.42 |
| IOS (MILLIAMPS) | 83.84 | 82.47 | 82.10 | 82.47 | 80.73 | 78.06 | 74.24 | 68.54 |
| IIL (MILLIAMPS) | 6.488 | 6.480 | 6.467 | 6.457 | 6.379 | 6.354 | 6.310 | 6.225 |
| IIH (MICROAMPS) | .38 | .37 | .36 | .28 | .23 | .16 | .11 | .10 |
| TPHL (NSEC-CLOCK) | 4.55 | 5.97 | 6.20 | 5.70 | 7.30 | 7.52 | 20.00 | 20.00 |
| TPHL (NSEC-CLEAR) | 13.57 | 13.30 | 13.27 | 14.75 | 14.15 | 11.52 | 6.22 | 9.65 |
| TPLH (NSEC-CLOCK) | 7.60 | 7.90 | 7.60 | 7.72 | 7.70 | 7.75 | 7.55 | 8.07 |
| TPLH (NSEC-PRESET) | 13.82 | 13.45 | 13.02 | 14.17 | 13.25 | 11.67 | 10.97 | 10.92 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN54S74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 | .12E+16 | .20E+16 |
|---|---|---|---|---|---|---|---|---|
| VOL (VOLTS) | .4440 | .4464 | .4537 | .4654 | .5199 | .5594 | .6253 | 1.6380 |
| VOH (VOLTS) | 2.848 | 2.801 | 2.785 | 2.780 | 2.756 | 2.771 | 2.740 | 2.389 |
| ICC (MILLIAMPS) | 35.95 | 35.92 | 35.81 | 35.64 | 35.00 | 34.57 | 34.02 | 35.09 |
| IOS (MILLIAMPS) | 84.56 | 83.25 | 82.87 | 83.20 | 80.73 | 77.67 | 73.66 | 67.79 |
| IIL (MILLIAMPS) | 6.287 | 6.284 | 6.270 | 6.252 | 6.146 | 6.148 | 6.104 | 6.028 |
| IIH (MICROAMPS) | .27 | .26 | .26 | .23 | .18 | .13 | .12 | .10 |
| TPHL (NSEC-CLOCK) | 5.65 | 5.62 | 6.62 | 6.70 | 9.70 | 7.67 | 7.60 | 7.50 |
| TPHL (NSEC-CLEAR) | 13.92 | 13.72 | 13.65 | 14.65 | 14.27 | 12.65 | 6.42 | 12.72 |
| TPLH (NSEC-CLOCK) | 7.70 | 7.85 | 7.80 | 7.60 | 7.70 | 7.72 | 8.02 | 8.07 |
| TPLH (NSEC-PRESET) | 13.65 | 13.35 | 12.70 | 12.85 | 12.87 | 11.85 | 10.72 | 10.20 |

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE SN54LS00T

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .3245 | .3259 | .3411 | .3647 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.580 | 3.577 | 3.566 | 3.535 | 3.4[illegible]0 | 3.351 |
| ICC (MILLIAMPS) | .66 | .66 | .65 | .64 | .62 | .61 |
| IOS (MILLIAMPS) | 14.46 | 14.46 | 14.28 | 14.13 | 13.56 | 12.92 |
| IIL (MILLIAMPS) | .159 | .159 | .157 | .156 | .151 | .148 |
| ITH (MICROAMPS) | .40 | .39 | .39 | .39 | .35 | .32 |
| TPHL (NANOSEC) | 14.15 | 14.40 | 15.12 | 16.07 | 20.17 | 25.37 |
| TPHL (NANOSEC) | 13.70 | 13.82 | 14.72 | 15.75 | 20.0[illegible] | 25.40 |
| TPLH (NANOSEC) | 16.92 | 16.92 | 17.07 | 17.32 | 18.42 | 19.90 |
| TPLH (NANOSEC) | 16.97 | 17.15 | 17.25 | 17.15 | 18.32 | 19.95 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN54LS00T

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .3210 | .3228 | .3367 | .3599 | 1.4930 | 1.6380 |
| VOH (VOLTS) | 3.591 | 3.580 | 3.577 | 3.547 | 3.475 | 3.388 |
| ICC (MILLIAMPS) | .68 | .68 | .67 | .67 | .65 | .63 |
| IOS (MILLIAMPS) | 14.59 | 14.59 | 14.44 | 14.29 | 13.77 | 13.19 |
| IIL (MILLIAMPS) | .161 | .162 | .160 | .159 | .154 | .150 |
| IIH (MICROAMPS) | .03 | .05 | .06 | .06 | .07 | .06 |
| TPHL (NANOSEC) | 14.25 | 14.15 | 14.77 | 15.82 | 18.95 | 23.87 |
| TPHL (NANOSEC) | 13.85 | 13.82 | 14.62 | 15.60 | 19.42 | 4.25 |
| TPLH (NANOSEC) | 17.00 | 16.70 | 16.57 | 17.12 | 18.10 | 19.35 |
| TPLH (NANOSEC) | 17.20 | 16.92 | 16.77 | 16.80 | 17.57 | 19.35 |

MEASUREMENTS ON DEVICE NUMBER 3. DEVICE TYPE SN54LS00T

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .3343 | .3367 | .3536 | .3796 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.582 | 3.578 | 3.564 | 3.532 | 3.439 | 3.341 |
| ICC (MILLIAMPS) | .63 | .64 | .63 | .62 | .60 | .59 |
| IOS (MILLIAMPS) | 14.27 | 14.28 | 14.14 | 13.99 | 13.46 | 12.79 |
| IIL (MILLIAMPS) | .152 | .153 | .151 | .150 | .145 | .142 |
| IIH (MICROAMPS) | .06 | .06 | .06 | .05 | .05 | .05 |
| TPHL (NANOSEC) | 14.47 | 14.70 | 15.52 | 16.35 | 20.90 | 26.60 |
| TPHL (NANOSEC) | 14.07 | 14.32 | 15.27 | 15.95 | 21.07 | 26.65 |
| TPLH (NANOSEC) | 17.65 | 17.32 | 17.67 | 17.65 | 18.90 | 20.67 |
| TPLH (NANOSEC) | 17.52 | 17.42 | 17.67 | 17.62 | 18.90 | 20.92 |

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

MEASUREMENTS ON DEVICE NUMBER 4, DEVICE TYPE SN54LS00T

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .3321 | .3335 | .3516 | .3719 | 1.6[illegible]80 | 1.6380 |
| VOH (VOLTS) | 3.569 | 3.564 | 3.547 | 3.524 | 3.428 | 3.318 |
| ICC (MILLIAMPS) | .69 | .70 | .69 | .68 | .66 | .65 |
| IOS (MILLIAMPS) | 14.80 | 14.80 | 14.63 | 14.51 | 13.86 | 13.12 |
| IIL (MILLIAMPS) | .168 | .169 | .167 | .166 | .161 | .157 |
| IIH (MICROAMPS) | .03 | .05 | .03 | .04 | .05 | .06 |
| TPHL (NANOSEC) | 14.20 | 14.42 | 14.92 | 16.11 | 20.12 | 26.15 |
| TPHL (NANOSEC) | 13.50 | 14.05 | 14.85 | 15.92 | 20.2[illegible] | 26.22 |
| TPLH (NANOSEC) | 16.85 | 16.52 | 16.70 | 16.52 | 18.35 | 19.95 |
| TPLH (NANOSEC) | 16.70 | 16.75 | 16.80 | 16.90 | 18.10 | 19.85 |

MEASUREMENTS ON DEVICE NUMBER 5, DEVICE TYPE SN54LS00T

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .3175 | .3196 | .3342 | .3553 | .8435 | 1.6380 |
| VOH (VOLTS) | 3.591 | 3.582 | 3.574 | 3.554 | 3.470 | 3.395 |
| ICC (MILLIAMPS) | .70 | .71 | .70 | .69 | .68 | .66 |
| IOS (MILLIAMPS) | 14.59 | 14.62 | 14.46 | 14.33 | 13.82 | 13.28 |
| IIL (MILLIAMPS) | .168 | .169 | .166 | .166 | .161 | .157 |
| IIH (MICROAMPS) | .07 | .04 | .06 | .06 | .07 | .07 |
| TPHL (NANOSEC) | 13.92 | 13.95 | 14.47 | 15.27 | 18.52 | 23.12 |
| TPHL (NANOSEC) | 13.32 | 13.40 | 14.10 | 15.05 | 18.45 | 23.52 |
| TPLH (NANOSEC) | 17.10 | 17.25 | 17.15 | 17.45 | 18.30 | 18.97 |
| TPLH (NANOSEC) | 17.52 | 17.35 | 17.50 | 17.02 | 17.72 | 19.42 |

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE SN54LS74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2647 | .2800 | .3191 | .3709 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.442 | 3.427 | 3.397 | 3.400 | 3.2[illegible]3 | 3.119 |
| ICC (MILLIAMPS) | 4.58 | 4.58 | 4.51 | 4.48 | 4.33 | 4.22 |
| IOS (MILLIAMPS) | 18.90 | 18.89 | 18.35 | 17.88 | 15.77 | 10.46 |
| IIL (MILLIAMPS) | 1.055 | 1.055 | 1.047 | 1.043 | 1.021 | 1.000 |
| IIH (MICROAMPS) | .61 | .60 | .24 | .19 | .17 | .15 |
| TPHL (NSEC-CLOCK) | 26.72 | 26.80 | 26.80 | 27.60 | 37.00 | 42.50 |
| TPHL (NSEC-CLEAR) | 32.57 | 32.32 | 31.90 | 34.47 | 45.40 | 55.00 |
| TPLH (NSEC-CLOCK) | 22.30 | 20.40 | 18.90 | 19.70 | 28.20 | 33.00 |
| TPLH (NSEC-PRESET) | 27.30 | 26.60 | 23.80 | 24.00 | 26.60 | 27.47 |

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE SN54LS74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2800 | .2924 | .3332 | .3845 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.439 | 3.425 | 3.393 | 3.391 | 3.253 | 3.116 |
| ICC (MILLIAMPS) | 4.55 | 4.55 | 4.49 | 4.46 | 4.32 | 4.21 |
| IOS (MILLIAMPS) | 17.67 | 17.64 | 17.13 | 16.68 | 14.57 | 10.13 |
| IIL (MILLIAMPS) | 1.039 | 1.039 | 1.036 | 1.035 | 1.017 | .996 |
| IIH (MICROAMPS) | .62 | .57 | .47 | .39 | .29 | .15 |
| TPHL (NSEC-CLOCK) | 27.85 | 27.40 | 26.17 | 27.10 | 35.90 | 43.80 |
| TPHL (NSEC-CLEAR) | 32.75 | 32.82 | 34.60 | 34.27 | 43.90 | 55.57 |
| TPLH (NSEC-CLOCK) | 23.60 | 21.60 | 19.00 | 19.10 | 27.80 | 32.32 |
| TPLH (NSEC-PRESET) | 27.60 | 28.30 | 24.50 | 25.30 | 26.70 | 27.00 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE SN54LS74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2390 | .2509 | .2778 | .3107 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.466 | 3.455 | 3.428 | 3.441 | 3.365 | 3.316 |
| ICC (MILLIAMPS) | 4.60 | 4.59 | 4.55 | 4.50 | 4.3[illegible] | 4.27 |
| IOS (MILLIAMPS) | 17.34 | 17.32 | 16.77 | 16.38 | 14.75 | 13.78 |
| IIL (MILLIAMPS) | 1.017 | 1.017 | 1.017 | 1.016 | 1.007 | .983 |
| IIH (MICROAMPS) | 1.50 | 1.38 | 1.29 | 1.14 | 1.10 | .61 |
| TPHL (NSEC-CLOCK) | 26.10 | 26.15 | 25.60 | 26.05 | 31.50 | 36.25 |
| TPHL (NSEC-CLEAR) | 33.62 | 33.80 | 32.55 | 33.62 | 29.02 | 43.00 |
| TPLH (NSEC-CLOCK) | 23.50 | 22.50 | 20.70 | 20.70 | 24.10 | 29.70 |
| TPLH (NSEC-PRESET) | 28.90 | 28.30 | 25.20 | 24.80 | 25.50 | 25.82 |

MEASUREMENTS ON DEVICE NUMBER 4, DEVICE TYPE SN54LS74J

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | .2392 | .2485 | .2747 | .3089 | 1.6380 | 1.6380 |
| VOH (VOLTS) | 3.466 | 3.448 | 3.427 | 3.434 | 3.375 | 3.321 |
| ICC (MILLIAMPS) | 4.62 | 4.62 | 4.56 | 4.53 | 4.40 | 4.28 |
| IOS (MILLIAMPS) | 17.30 | 17.27 | 16.74 | 16.32 | 14.68 | 13.70 |
| IIL (MILLIAMPS) | 1.024 | 1.026 | 1.022 | 1.025 | 1.018 | .996 |
| IIH (MICROAMPS) | .32 | .27 | 1.25 | 1.07 | .96 | .58 |
| TPHL (NSEC-CLOCK) | 23.00 | 21.50 | 19.30 | 18.30 | 22.90 | 28.60 |
| TPHL (NSEC-CLEAR) | 32.10 | 32.00 | 31.15 | 33.95 | 38.20 | 42.20 |
| TPLH (NSEC-CLOCK) | 24.72 | 24.30 | 23.30 | 24.10 | 30.70 | 35.02 |
| TPLH (NSEC-PRESET) | 28.30 | 28.10 | 25.40 | 25.20 | 25.90 | 25.75 |

MEASUREMENTS ON DEVICE NUMBER 1, DEVICE TYPE 952859

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | -1.732 | -1.747 | -1.733 | -1.708 | -1.647 | -1.525 |
| VOH (VOLTS) | -.939 | -.955 | -.960 | -.954 | -.971 | -.991 |
| ICC (MILLIAMPS) | 71.53 | 71.13 | 69.69 | 69.24 | 67.50 | 60.48 |
| IIL (MILLIAMPS) | 1.81 | 1.81 | 1.80 | 1.82 | 1.83 | 1.86 |
| IIH (MILLIAMPS) | 2.25 | 2.25 | 2.25 | 2.27 | 2.30 | 2.40 |
| TPHL (NSEC-CLOCK) | 3.75 | 3.15 | 3.32 | 3.55 | 2.27 | 1.70 |
| TPHL (NSEC-CLEAR) | 3.60 | 3.95 | 3.97 | 4.02 | 3.07 | 2.42 |
| TPLH (NSEC-CLOCK) | 4.02 | 4.42 | 4.40 | 4.37 | 3.45 | 2.28 |
| TPLH (NSEC-PRESET) | 7.52 | 4.82 | 4.62 | 5.62 | 3.85 | 2.97 |

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE 95[illegible]859

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | -1.740 | -1.736 | -1.718 | -1.684 | -1.592 | -1.434 |
| VOH (VOLTS) | -.943 | -.956 | -.963 | -.974 | -.995 | -1.058 |
| ICC (MILLIAMPS) | 65.69 | 63.16 | 61.70 | 60.68 | 61.1[illegible] | 48.96 |
| IIL (MILLIAMPS) | 1.83 | 1.77 | 1.77 | 1.79 | 1.84 | 1.91 |
| IIH (MILLIAMPS) | 2.28 | 2.20 | 2.21 | 2.24 | 2.33 | 2.48 |
| TPHL (NSEC-CLOCK) | 3.67 | 3.52 | 3.60 | 4.05 | 2.45 | 1.52 |
| TPHL (NSEC-CLEAR) | 4.20 | 4.10 | 4.10 | 4.20 | 2.85 | 4.00 |
| TPLH (NSEC-CLOCK) | 4.60 | 4.62 | 4.35 | 4.25 | 2.70 | 1.80 |
| TPLH (NSEC-PRESET) | 5.42 | 5.40 | 4.72 | 4.55 | 3.2[illegible] | 3.07 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE 952859

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | -1.745 | -1.734 | -1.716 | -1.681 | -1.599 | -1.438 |
| VOH (VOLTS) | -.958 | -.957 | -.960 | -.964 | -.988 | -1.044 |
| ICC (MILLIAMPS) | 66.43 | 64.96 | 63.75 | 63.53 | 63.47 | 51.16 |
| IIL (MILLIAMPS) | 1.79 | 1.83 | 1.84 | 1.86 | 1.82 | 1.96 |
| IIH (MILLIAMPS) | 1.99 | 2.29 | 2.30 | 2.33 | 2.39 | 2.55 |
| TPHL (NSEC-CLOCK) | 4.32 | 3.37 | 3.50 | 3.67 | 2.32 | 1.42 |
| TPHL (NSEC-CLEAR) | 4.10 | 3.75 | 3.95 | 4.02 | 2.75 | 1.30 |
| TPLH (NSEC-CLOCK) | 4.62 | 4.72 | 4.42 | 4.37 | 2.77 | 1.65 |
| TPLH (NSEC-PRESET) | 5.30 | 5.02 | 4.67 | 4.50 | 3.32 | 2.20 |

MEASUREMENTS ON DEVICE NUMBER 1. DEVICE TYPE MC10131L

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | -1.753 | -1.753 | -1.753 | -1.717 | -1.662 | -1.592 |
| VOH (VOLTS) | -.866 | -.873 | -.906 | -.907 | -.909 | -1.056 |
| ICC (MILLIAMPS) | 35.94 | 35.71 | 34.50 | 34.22 | 32.53 | 31.09 |
| IIL (MICROAMPS) | 16.00 | 16.37 | 27.50 | 39.18 | 75.22 | 133.02 |
| IIH (MILLIAMPS) | .02 | .02 | .03 | .05 | .10 | .12 |
| TPHL (NSEC-CLOCK) | 3.35 | 2.57 | 3.12 | 4.05 | 2.62 | 2.32 |
| TPHL (NSEC-CLEAR) | 3.35 | 3.67 | 3.92 | 4.65 | 3.72 | 3.27 |
| TPLH (NSEC-CLOCK) | 5.65 | 5.70 | 5.07 | 5.17 | 4.23 | 3.65 |
| TPLH (NSEC-PRESET) | 5.52 | 5.30 | 5.17 | 5.32 | 3.95 | 3.67 |

MEASUREMENTS ON DEVICE NUMBER 2, DEVICE TYPE MC10131L

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | -1.759 | -1.760 | -1.759 | -1.727 | -1.653 | -1.608 |
| VOH (VOLTS) | -.870 | -.873 | -.913 | -.919 | -.990 | -1.115 |
| ICC (MILLIAMPS) | 35.71 | 35.48 | 34.28 | 34.00 | 32.03 | 30.90 |
| IIL (MICROAMPS) | 18.82 | 19.82 | 30.41 | 41.23 | 70.32 | 131.15 |
| IIH (MILLIAMPS) | .02 | .02 | .03 | .04 | .0[illegible] | .11 |
| TPHL (NSEC-CLOCK) | 2.87 | 2.70 | 3.50 | 3.87 | 2.45 | 2.30 |
| TPHL (NSEC-CLEAR) | 3.32 | 3.87 | 4.00 | 4.75 | 3.42 | 3.32 |
| TPLH (NSEC-CLOCK) | 5.72 | 5.75 | 5.35 | 5.17 | 4.15 | 3.77 |
| TPLH (NSEC-PRESET) | 5.86 | 5.35 | 5.40 | 5.40 | 4.02 | 3.80 |

MEASUREMENTS ON DEVICE NUMBER 3, DEVICE TYPE MC10131L

| TEST | PRE RAD | .28E+13 | .69E+14 | .14E+15 | .46E+15 | .73E+15 |
|---|---|---|---|---|---|---|
| VOL (VOLTS) | -1.721 | -1.721 | -1.713 | -1.679 | -1.606 | -1.557 |
| VOH (VOLTS) | -.912 | -.917 | -.954 | -.967 | -1.068 | -1.130 |
| ICC (MILLIAMPS) | 36.97 | 36.77 | 35.40 | 34.96 | 32.53 | 30.73 |
| IIL (MICROAMPS) | 60.65 | 62.56 | 77.06 | 93.83 | 150.68 | 239.86 |
| IIH (MILLIAMPS) | .08 | .08 | .09 | .11 | .17 | .21 |
| TPHL (NSEC-CLOCK) | 3.17 | 3.02 | 3.60 | 4.22 | 2.72 | 2.20 |
| TPHL (NSEC-CLEAR) | 3.42 | 3.67 | 3.50 | 4.72 | 3.75 | 3.10 |
| TPLH (NSEC-CLOCK) | 5.52 | 5.60 | 5.40 | 5.12 | 4.07 | 3.25 |
| TPLH (NSEC-PRESET) | 5.47 | 5.47 | 5.37 | 5.27 | 4.42 | 3.42 |

## DISTRIBUTION LIST

DEPARTMENT OF DEFENSE

Director
Armed Forces Radiobiology Research Institute
Defense Nuclear Agency
National Naval Medical Center
ATTN: Technical Library

Commander in Chief
U.S. European Command
ATTN: FCJ6-PF

Defense Communication Engineer Center
ATTN: Code R320, C. Bergman
ATTN: Code R410, J. McLean

Director
Defense Communications Agency
ATTN: Code 930, M. Burgett, Jr.

Defense Documentation Center
Cameron Station
12 cy ATTN: TC

Director
Defense Intelligence Agency
ATTN: DS-4A2

Director
Defense Nuclear Agency
ATTN: TITL
ATTN: DDST
ATTN: RAEV

Commander
Field Command
Defense Nuclear Agency
ATTN: FCPR

Director
Interservice Nuclear Weapons School
ATTN: Document Control

Director
Joint Strat. Tgt. Planning Staff
ATTN: JLTW-2

Chief
Livermore Division, Fld. Command, DNA
Lawrence Livermore Laboratory
ATTN: FCPRL

Director
National Security Agency
ATTN: D. Vincent
ATTN: TDL
ATTN: O. Van Gunten, R-425

OJCS/J-3
ATTN: J-3, RDTA, BR, WWMCCS, Plans Div.

Under Secretary of Def. for Rsch. & Engrg.
ATTN: S&SS (OS)
ATTN: AE

DEPARTMENT OF THE ARMY

Project Manager
Army Tactical Data Systems
U.S. Army Electronics Command
ATTN: D. Huewe
ATTN: DRCPN-TDS-SD

Commander
BMD System Command
ATTN: BDMSC-TEN, N. Hurst

Commander
ERADCOM Technical Support Directorate
ATTN: DRSEL-GG-TD, W. Werk
ATTN: DRSEL-CT-HDK, A. Cohen
ATTN: DRSEL-CE, T. Preiffer
ATTN: DRSEL-PL-ENV, H. Bomke
ATTN: DRSEL-TL-TR, E. Hunter
ATTN: DRSEL-TL-MD, G. Gaule
ATTN: DRSEL-TL-ND, S. Kronenbey

Commander
Harry Diamond Laboratories
ATTN: DELHD-RCC, J. Rosado
ATTN: DELHD-RCC, J. Thompkins
ATTN: DELHD-TI, Tech. Lib.
ATTN: DELHD-EM, R. McCoskey
ATTN: DELHD-TF, R. Oswald, Jr.
ATTN: DELHD-EM, R. Bostak
ATTN: DELHD-EM, J. McGarrity
ATTN: DELHD-EM, J. Halpin
ATTN: DELHD-RB, J. Miletta
ATTN: DELHD-EM, J. Reilfuss
ATTN: DELHD-NP, F. Wimenitz
ATTN: DELHD-EM, R. Gray
ATTN: DELHD-EM, R. Wong

Commanding Officer
Night Vision Laboratory
U.S. Army Electronics Command
ATTN: CPT A. Parker

Commander
Redstone Scientific Information Ctr.
U.S. Army Missile Command
3 cy ATTN: Chief, Documents

Secretary of the Army
ATTN: ODUSA or D. Willard

Director
TRASANA
ATTN: ATAA-EAC, F. Winans

Director
U.S. Army Ballistic Research Labs.
ATTN: DRXBR-VL, J. Kinch
ATTN: DRXBR-X, J. Meszaros
ATTN: DRXBR-AM, W. Vanantwerp
ATTN: DRXBR-VL, R. Harrison
ATTN: DRXBR-BYL, D. Rigotti

Chief
U.S. Army Communications Sys. Agency
ATTN: SCCM-AD-SV, Library

DEPARTMENT OF THE ARMY (Continued)

Commander
U.S. Army Electronics Proving Ground
ATTN: STEEP-MT-M, G. Durbin

Commandant
U.S. Army Engineer School
ATTN: ATSE-CTD-CS, S. Grazier

Commander-in-Chief
U.S. Army Europe and Seventh Army
ATTN: ODCSE-E, AFAGF-PI

Commandant
U.S. Army Field Artillery School
ATTN: ATSFA-CTD-ME, H. Moberg

Commander
U.S. Army Mat. & Mechanics Rsch. Ctr.
ATTN: DRXMR-HH, J. Dignam

Commander
U.S. Army Materiel Dev. & Readiness Cmd.
ATTN: DRCDE-D, L. Flynn

Commander
U.S. Army Missile R&D Command
ATTN: DRCPM-PE-EA, W. Wagner
ATTN: DRSMI-RGD, V. Ruwe
ATTN: DRSMI-RGP, H. Green

Chief
U.S. Army Nuc. and Chemical Surety Gp.
ATTN: MOSG-ND, MAJ S. Winslow

Commander
U.S. Army Nuclear & Chemical Agency
ATTN: Library

Commander
U.S. Army Tank Automotive Command
ATTN: DRCPM-GCM-SW, L. Wolcott

Commander
U.S. Army Test and Evaluation Comd.
ATTN: DRSTE-EL, R. Kolchin
ATTN: DRSTE-NB, R. Galasso

Commander
White Sands Missile Range
ATTN: STEWS-TE-NT, M. Squires

DEPARTMENT OF THE NAVY

Chief of Naval Research
ATTN: Code 427

Commanding Officer
Naval Avionics Facility
ATTN: Branch 942, D. Repass

Commander
Naval Electronic Systems Command
Naval Electronic Systems Cmd. Hqs.
ATTN: Code 5032, C. Neill
ATTN: ELEX 05323, C. Watkins
ATTN: PME 117-21
ATTN: Code 504511, C. Suman
ATTN: Code 50451

DEPARTMENT OF THE NAVY (Continued)

Commanding Officer
Naval Intelligence Support Ctr.
ATTN: NISC-45

Commander
Naval Ocean Systems Center
ATTN: H. Wong

Director
Naval Research Laboratory
ATTN: Code 5210, J. Davey
ATTN: Code 2627, D. Folen
ATTN: Code 4104, E. Brancato
ATTN: Code 5580, G. Sigel
ATTN: Code 5216, H. Hughes
ATTN: Code 601, F. Wolicki
ATTN: Code 6701, J. Brown
ATTN: Code 6631, J. Ritter

Commander
Naval Sea Systems Command
ATTN: SEA-9931, R. Lane
ATTN: SEA-9931, S. Barham

Officer-in-Charge
Naval Surface Weapons Center
ATTN: Code WA501, Navy Nuc. Prgms. Off.
ATTN: Code WA52, R. Smith
ATTN: Code WA50

Commander
Naval Surface Weapons Center
Dahlgren Laboratory
ATTN: Code FUR, R. Amadori

Commander
Naval Weapons Center
ATTN: Code 533, Tech. Lib.

Commanding Officer
Naval Weapons Evaluation Facility
ATTN: Code ATG, Mr. Stanley

Commanding Officer
Naval Weapons Support Center
ATTN: Code 7024, J. Ramsey
ATTN: Code 70242, J. Numarin

Commanding Officer
Nuclear Weapons Tng. Center, Pacific
Naval Air Station, North Island
ATTN: Code 50

Director
Strategic Systems Project Office
ATTN: NSP-2342, R. Coleman
ATTN: SP 2701, J. Pitsenberger
ATTN: NSP-27331, P. Spector

DEPARTMENT OF THE AIR FORCE

AF Aero-Propulsion Laboratory, AFSC
ATTN: POD, P. Stover

AF Institute of Technology, AU
ATTN: ENP, C. Bridgman

AF Materials Laboratory, AFSC
ATTN: LTE

DEPARTMENT OF THE AIR FORCE (Continued)

AF Weapons Laboratory, AFSC
ATTN: ELS
ATTN: ELA
ATTN: ELP, Tree Section
ATTN: NT, C. Baum
ATTN: ELP, J. Nichols
ATTN: NTS
ATTN: ELXT
ATTN: DEX
2 cy ATTN: SUL
ATTN: HO, Dr. Minge
10 cy ATTN: ELP, Lt M. Knoll, Project Officer

AFTAC
ATTN: TFS, Maj M. Schneider
ATTN: TAE

Air Force Avionics Laboratory, AFSC
ATTN: AAT, M. Friar
ATTN: DHM, C. Friend
ATTN: DH, Lt Col McKenzie
ATTN: DHE, H. Hennecke

Commander
ASD
ATTN: ASD/ENESS, P. Marth
ATTN: ASD-YH-EX, Lt Col R. Leverette
ATTN: ENACC, R. Fish

Headquarters
Electronic Systems Division/YSEA
ATTN: YSEA

Headquarters
Electronic Systems Division/YW
ATTN: YWEI

Commander
Foreign Technology Division, AFSC
ATTN: FTD/PDJC
ATTN: ETDP

Commander
Ogden ALC/MMEDDE
ATTN: MMETH, R. Joffs

Commander
Rome Air Development Center, AFSC
ATTN: RBRAC, I. Krulac
ATTN: RBRP, C. Lane

Commander
Rome Air Development Center, AFSC
ATTN: ESR, B. Buchanan
ATTN: ESD, A. Kahan
ATTN: ETS, R. Dolan

SAMSO/DY
ATTN: DYS, Capt E. Merz

SAMSO/MN
ATTN: MNNH

SAMSO/RS
ATTN: RSMG, Capt Collier
ATTN: RSSE, Lt Col K. Gilbert

SAMSO/SK
ATTN: SKE, P. Stadler

DEPARTMENT OF THE AIR FORCE (Continued)

SAMSO/SZ
ATTN: SZJ, Capt J. Salch

Commander in Chief
Strategic Air Command
ATTN: XPFS, Maj B. Stephan
ATTN: NRI-STINFO, Library

Air University Library
ATTN: LDE

DEPARTMENT OF ENERGY

Department of Energy
Albuquerque Operations Office
ATTN: Document Control for WSSB

University of California
Lawrence Livermore Laboratory
ATTN: R. Ott, L-531
ATTN: W. Hogan, L-389
ATTN: J. Keller, Jr., L-125
ATTN: F. Kovar, L-31
ATTN: D. Meeker, L-545
ATTN: E. Miller, L-156
ATTN: Tech. Info., Dept. L-3
ATTN: H. Kruger, L-96
ATTN: L. Cleland, L-156

Los Alamos Scientific Laboratory
ATTN: Doc. Con. for B. Noel
ATTN: Doc. Con. for J. Freed

Sandia Laboratories
ATTN: Doc. Con. for Org. 2110, J. Hood
ATTN: Doc. Con. for 3141, Sandia Rpt. Coll.
ATTN: Doc. Con. for Org. 2140, R. Gregory

OTHER GOVERNMENT AGENCY

Department of Commerce
National Bureau of Standards
ATTN: J. French

DEPARTMENT OF DEFENSE CONTRACTORS

Aerojet Electro-Systems Co.
Div. of Aerojet-General Corporation
ATTN: T. Hanscome

Aerospace Corporation
ATTN: J. Reinheimer
ATTN: I. Garfunkel
ATTN: S. Bower
ATTN: Library
ATTN: L. Aukerman
ATTN: J. Ditre
ATTN: W. Willis

Avco Research & Systems Group
ATTN: Research Lib. A830, Rm. 7201

The BDM Corporation
ATTN: D. Alexander

The Bendix Corporation
Communication Division
ATTN: Document Control

AD-A058 093 AIR FORCE WEAPONS LAB KIRTLAND AFB N MEX F/G 9/5
COMPARISON STUDY OF THE FIVE TRANSISTOR-TRANSISTOR-LOGIC (TTL) --ETC(U)
MAY 78 M G KNOLL
UNCLASSIFIED AFWL-TR-78-5 NL

2 OF 2
AD
A058 093

END
DATE
FILMED
10-78
DDC


1.0
1.1
1.25
1.4
1.6
1.8
2.0
2.2
2.5
2.8
3.2
3.6
4.0
MICROCOPY RESOLUTION TEST CHART

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

The Bendix Corporation
Research Laboratories Division
Bendix Center
ATTN: Mgr. Prgm. Dev., D. Niehaus
ATTN: M. Frank

The Boeing Company
ATTN: H. Wicklein, MS 17-11
ATTN: Aerospace Library
ATTN: D. Egelkrout, MS 2R-00
ATTN: I. Amura, 2R-00
ATTN: R. Caldwell, 2R-00
ATTN: C. Rosenbert, 2R-00

Booz-Allen and Hamilton, Inc.
ATTN: R. Chrisner

California Institute of Technology
Jet Propulsion Laboratory
ATTN: J. Bryden
ATTN: A. Stanley

Charles Stark Draper Laboratory, Inc.
ATTN: P. Kelly
ATTN: K. Fertig

Cincinnati Electronics Corporation
ATTN: C. Stump
ATTN: L. Hammond

Control Data Corporation
ATTN: J. Meehan

Cutler-Hammer, Inc.
Ail Division
ATTN: Central Tech. Files, A. Anthony

University of Denver
Colorado Seminary
Denver Research Institute
ATTN: Sec. Officer for F. Venditti

Dikewood Industries, Inc.
ATTN: L. Davis

E-Systems, Inc.
Greenville Division
ATTN: Library 8-50100

Effects Technology, Inc.
ATTN: E. Steele

EXP & Math Physics Consultants
ATTN: T. Jordan

Fairchild Camera and Instrument Corp.
ATTN: Sec. Dept. for 2-233, D. Myers

Fairchild Industries, Inc.
Sherman Fairchild Technology Center
ATTN: Mgr. Config. Data & Standards

University of Florida
ATTN: P. Rambo for D. Kennedy

Ford Aerospace & Communications Corp.
ATTN: D. McMorrow, MS G30
ATTN: E. Hahn, MS-X22
ATTN: S. Crawford, MS 531

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

Ford Aerospace & Communications Operations
ATTN: Tech. Info. Section
ATTN: K. Attinger
ATTN: F. Poncelet, Jr.

The Franklin Institute
ATTN: R. Thompson

Garrett Corporation
ATTN: R. Weir, Dept. 93-9

General Electric Company
Space Division
Valley Forge Space Center
ATTN: L. Chasen
ATTN: J. Peden, VFSC, Rm. 4230M
ATTN: J. Andrews

General Electric Company
Re-Entry & Environmental Systems Div.
ATTN: R. Benedict
ATTN: W. Patterson
ATTN: J. Palcheesky, Jr.

General Electric Company
Ordnance Systems
ATTN: J. Reidl

General Electric Company
TEMPO-Center for Advanced Studies
ATTN: M. Espig
ATTN: W. McNamera
ATTN: R. Rutherford
ATTN: DASIAC

General Electric Company
Aircraft Engine Business Group
ATTN: J. Ellerhorst, E2

General Electric Company
Aerospace Electronics Systems
ATTN: C. Hewison, Drop 624

General Electric Company
ATTN: D. Pepin, Drop 160

General Electric Company-TEMPO
ATTN: DASIAC for W. Alfonte

General Research Corporation
ATTN: R. Hill

Georgia Institute of Technology
Georgia Tech. Research Institute
ATTN: R. Curry

Grumman Aerospace Corporation
ATTN: J. Rogers, Dept. 533

GTE Sylvania, Inc.
Electronics Systems Grp.-Eastern Div.
ATTN: C. Thornhill, Librarian
ATTN: L. Blaisdell
ATTN: J. Waldon

GTE Sylvania, Inc.
ATTN: H & V Group
ATTN: P. Fredrickson
ATTN: J. Waldron
ATTN: H. Ullman
ATTN: C. Ramsbottom

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

Gulton Industries, Inc.
Engineered Magnetics Division
ATTN: Engnmagnetics Div.

Harris Corporation
Harris Semiconductor Division
ATTN: T. Clark, MS 4040

Hazeltine Corporation
ATTN: Tech. Info. Ctr., M. Waite

Honeywell Incorporated
Avionics Division
ATTN: R. Johnson, A1622
ATTN: R. Kell, MS S2572

Honeywell Incorporated
Avionics Division
ATTN: S. Graff, MS 725-5
ATTN: H. Noble, MS 725-5A

Honeywell Incorporated
Radiation Center
ATTN: Technical Library

Hughes Aircraft Company
ATTN: K. Walker, MS Dis7
ATTN: B. Campbell, MS 6-E-110
ATTN: D. Binder, MS 6-D147
ATTN: J. Singletary, MS 6-D133

Hughes Aircraft Company
El Segundo Site
ATTN: E. Smith, MS A620
ATTN: W. Scott, MS A1080

IBM Corporation
ATTN: F. Frankovsky
ATTN: H. Mathers, Dept. M41

IIT Research Institute
ATTN: I. Mindel

Intl. Tel. & Telegraph Corporation
ATTN: A. Richardson

Ion Physics Corporation
ATTN: R. Evans

IRT Corporation
ATTN: MDC
ATTN: R. Mertz

JAYCOR
ATTN: E. Wenaas

JAYCOR
ATTN: R. Sullivan
ATTN: C. Turesko

Johns Hopkins University
Applied Physics Laboratory
ATTN: P. Partridge

Kaman Sciences Corporation
ATTN: A. Bridges
ATTN: J. Hoffman
ATTN: D. Bryce
ATTN: J. Lubell
ATTN: W. Rich
ATTN: W. Ware

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

Litton Systems, Inc.
Guidance & Control Systems Division
ATTN: R. Maughmer
ATTN: J. Retzler
ATTN: V. Ashby, MS 67
ATTN: W. Mras

Litton Systems, Inc.
Electron Tube Division
ATTN: F. McCarthy

Lockheed Missiles & Space Co., Inc.
ATTN: B. Kimura, Dept. 81-14
ATTN: G. Heath, D/81-14
ATTN: E. Smith, D/85-85
ATTN: S. Taimuty, D/85-85
ATTN: L. Rossi, D/81-64

Lockheed Missiles and Space Co., Inc.
ATTN: Tech. Info. Ctr., D/Coll.

M.I.T. Lincoln Laboratory
ATTN: L. Loughlin, Librarian A-082

Martin Marietta Corporation
Orlando Division
ATTN: J. Ashford, MP-537
ATTN: M. Griffith, Lib. MP-30

Martin Marietta Corporation
Denver Division
ATTN: B. Graham, MS PO-454
ATTN: P. Kase, Mail 8203
ATTN: Research Lib. 6617, J. McKee
ATTN: J. Goodwin, Mail 0452

McDonnell Douglas Corporation
ATTN: Technical Library
ATTN: T. Ender

McDonnell Douglas Corporation
ATTN: S. Schneider

McDonnell Douglas Corporation
ATTN: Technical Library, C1-290/36-84

Mission Research Corporation
ATTN: W. Hart

Mission Research Corporation
EM System Applications Division
ATTN: D. Merewether

Mission Research Corporation-San Diego
ATTN: J. Raymond
ATTN: V. Van Lint

The Mitre Corporation
ATTN: M. Fitzgerald

National Academy of Sciences
ATTN: National Materials Advisory Board for
R. Shane, Nat. Materials Advsy.

University of New Mexico
Electrical Engineering & Computer Science Dept.
ATTN: H. Southward

Northrop Corporation
Electronic Division
ATTN: G. Towner

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

Northrop Corporation
Northrop Research and Technology Ctr.
ATTN: O. Curtis, Jr.
ATTN: J. Srour
ATTN: D. Pocock

Northrop Corporation
Electronic Division
ATTN: J. Russo
ATTN: V. Demartino
ATTN: R. Ahlport

Palisades Inst. for Rsch. Services, Inc.
ATTN: Records Supervisor

Physics International Company
ATTN: Doc. Con. for C Stallings
ATTN: Doc. Con. for J. Huntington

R & D Associates
ATTN: S. Rogers

The Rand Corporation
ATTN: C. Crain

Raytheon Company
ATTN: G. Joshi, Radar Sys. Lab.

Raytheon Company
ATTN: H. Flescher

RCA Corporation
Government Systems Division
Astro Electronics
ATTN: G. Brucker

RCA Corporation
Camden Complex
ATTN: E. Van Keuren, 13-5-2

Rensselaer Polytechnic Institute
ATTN: R. Gutmann

Research Triangle Institute
ATTN: Eng. Div., M. Simons, Jr.

Rockwell International Corporation
ATTN: K. Hull
ATTN: N. Rudie, FA53
ATTN: D. Stevens, FA70
ATTN: G. Messenger, FB61
ATTN: J. Bell, HA10

Rockwell International Corporation
ATTN: T. Yates

Rockwell International Corporation
Collins Divisions
ATTN: A. Langenfeld

Sanders Associates, Inc.
ATTN: M. Aitel, NCA 1-3236

Science Applications, Inc.
ATTN: W. Chadsey

Science Applications, Inc.
ATTN: F. Tesche

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

Science Applications, Inc.
ATTN: J. Beyster

Science Applications, Inc.
Huntsville Division
ATTN: N. Byrn

Science Applications, Inc.
ATTN: J. Hill

The Singer Company (Data Systems)
ATTN: Tech. Info. Center

The Singer Company
ATTN: Security Manager for I. Goldman, Eng. Management

Sperry Flight Systems Division
Sperry Rand Corporation
ATTN: D. Schow

Sperry Rand Corporation
Sperry Division
ATTN: P. Maraffino
ATTN: C. Craig, EV

Sperry Univac
ATTN: J. Inda, MS 41T25

SRI International
ATTN: P. Dolan
ATTN: A. Whitson

SRI International
ATTN: M. Morgan

Sundstrand Corporation
ATTN: C. White

Systron-Donner Corporation
ATTN: G. Dean
ATTN: H. Morris

Texas Instruments, Inc.
ATTN: D. Manus, MS 72

Texas Tech University
ATTN: T. Simpson

TRW Defense & Space Sys. Group
One Space Park
2 cy ATTN: R. Plebuch, R1-2078
ATTN: H. Holloway, R1-2036
ATTN: Tech. Info. Center/S-1930
2 cy ATTN: O. Adams, R1-1144

TRW Defense & Space Sys. Group
San Bernardino Operations
ATTN: F. Fay
ATTN: R. Kitter

United Technologies Corporation
Hamilton Standard Division
ATTN: R. Giguere

Vought Corporation
ATTN: Technical Data Ctr.

Westinghouse Electric Corporation
Defense and Electronic Systems Ctr.
ATTN: H. Kalapaca, MS 3525